

SQA-8448 JUNCTION TRAFFIC SIGNAL DESIGN SHEET PART A

Site Ref:	12/854 (12/049)	Revision No:	I	Date:	01/11/2019
Address:	King's Road / Edith Grove				
SI Engineer:		WBS Code:			
Drawing Number:	RWA-19-20-176-12-049	Primary Mode:	SCOOT UTC		
UID:		Fallback Mode:	CLF		

Parallel Stage Stream Site Refs (if Applicable)
 12/855 (12/194) & 12/856 (12/208)


Reason For Changes/Update
 Temporary lights for civils works to be undertaken (Under CLF streams will run leaving amber link)

EXISTING LIVE DESIGN INFORMATION

Item	Source	Version	File Location (Hyperlink)
Existing Staging	Controller Spec	II	Here
Existing Phases	Controller Spec	II	Here
Existing Stage Moves	Controller Spec	II	Here
Existing Intergreens	Controller Spec	II	Here
Existing Phase Delays	Controller Spec	II	Here
Existing CLF/Timetabl	Controller Spec	II	Here
UTC Pattern	Controller Spec	II	Here

Is there any live design information which cannot be indicated above? No

PROPOSED STAGING



Are there any changes to stages? Yes

SQA-8448 JUNCTION TRAFFIC SIGNAL DESIGN SHEET PART A

Site Ref: 12/854 (12/049) Revision No: I Date: 01/11/2019
 Address: King's Road / Edith Grove

(Not on OTU - do not include in UTC Word)

PROPOSED UTC LINK
(On OTU - include in UTC Word)

PROPOSED UTC MODE DEPENDANCY (STREAMS)

Linked Site

Linked Site
12/855
12/856

	0	1	2	3	4
0					
1	X				
2	X				
3	X				
4					

PROPOSED PHASE DELAYS

No.	Phase	From	To	Secs	No.	Phase	From	To	Secs	No.	Phase	From	To	Secs	No.	Phase	From	To	Secs
0	A	1	3	4	24					48					72				
1	B	1	3	4	25					49					73				
2	C	3	1	2	26					50					74				
3	C	3	5	1	27					51					75				
4					28					52					76				
5					29					53					77				
6					30					54					78				
7					31					55					79				
8					32					56					80				
9					33					57					81				
10					34					58					82				
11					35					59					83				
12					36					60					84				
13					37					61					85				
14					38					62					86				
15					39					63					87				
16					40					64					88				
17					41					65					89				
18					42					66					90				
19					43					67					91				
20					44					68					92				
21					45					69					93				
22					46					70					94				
23					47					71					95				

Are there any changes to phase delays Yes

PROPOSED LEAVING AMBER LINKS

Link No	Link to Ped	Associated Stage or Phase	Start or End	Link Delay Time	Inhibit Release Period	Override Time
0	12/855 (12/194)	A	End	5	2	180
1	12/856 (12/208)	C	End	5	2	180
2						
3						

"Fixed Time to Current Max" to be Used as Last Mode in Priority, Unless Otherwise Stated Below

Additional Notes:

LA links to run in all modes except UTC. (Under CLF streams will run leaving amber LINK)
 Latched demands to be configured that a demand from PBII puts in demand for phase H

	Role:	Name:	Date:
(ENG) S1 Engineer:	Senior Engineer	██████████	01/11/2019
(ENG) S2 Engineer:	Safety Checker	██████████	04/11/2019

SQA-8448 JUNCTION TRAFFIC SIGNAL DESIGN SHEET PART A

Site Ref: Revision No: Date:
 Address:

PROPOSED INTERSTAGE TABLE

iBUS LOCAL EXTENSION TIMERS

	TO																
	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FROM	0	2	2	2													
	1	4		6	10												
	2	3	x		6												
	3	4	10	10													
	4					2	2										
	5				3		5										
	6				3	8											
	7							2	2								
	8						3		5								
	9						3	8									
	10									2	2						
	11								3		5						
	12								3	8							
	13																
	14																
	15																
	16																

Is EP/EC configured?

Are there any interstage changes?

PROPOSED UTC CONTROL / REPLY WORD

Please mark all demand dependent stages with a #

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
CONTROL	1F1	#1F2	1F3	1F4	1F5	1F6	ITS				2F1	#2F2	2DX	3F1	#3F2	3DX
REPLY	1G1	1G2	1G3	1G4	1G5	1G6	1RT	1JL	1JD	1RF1	2G1	2G2	1RF2	3G1	3G2	
	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
REPLY																

RTC SYNC TIME

Are there any changes to the UTC control/reply word?

NETWORK PERFORMANCE DEPARTMENT CONSIDERATIONS

What Modelling Has Been Produced?

(Please include Hyperlink to modelling location)

Additional Information:-

Latched demands to be configured such that a demand from PBI 1 puts in demand for phase H - NPD
 Latched demand to be configured such that a demand from PB2 puts in a forward demand for phase L but the forward demand is only entered after the start of phase M in order to ensure that a demand is not entered for phase L before phase M has started.

	Role:	Name:	Date:
(NPD) Checker:	Senior Network Manager		
(NPD) Approver:	Principal Network Manager		