EARTH BONDS TO BE ADDED TO OUTER ENDS OF ALL BOGIES AS FOLLOWS:
ALL BOGIES:- LUG, DRG 42201, ITEM 51 TO BE WELDED TO BOGIE FRAME AS SHOWN (2 PER BOGIE)
MOTOR BOGIES :- EDE TERMINAL PLATE, DRG 38852 ITEM 5, SECURED TO AXLEBOXES USING EXISTING BOLTS AS SHOWN (2 PER BOGIE)
TRAILER BOGIES :- USE BOLT, DRG 43564, ITEM 14, IN OUTER AXLEBOXES AS USED IN INNER AXLEBOXES (2 PER BOGIE)
EXISTING BRASS BOLTS, DRG 3057, ITEM 6, & EARTH BOND ASSY. DRG. 38852/7, TO BE USED.











DIAGRAMATIC PLAN SHOWING SHOEGEAR & TRIPCOCK. (MOTOR CARS) & POSITION OF EARTHBONDS (MOTOR & TRAILER CARS)

	MODIFICATIONS
E	MET CRS 2222 NOTES RE "FOR REPLACEMENT POS ARC SPLASH BARRIER ETC.....°" AND "FOR FUTURE...°" ADDED. JH 12/99
D	Mod 12105 Dim 2808 – 83992/01 was 43595/10 (M) HY 5/8/93
C	MOD 9452, 3 OFF AXLE TO PANNE EARTH BONDS REMOVED PER INDUSTRIAL LSSD DRAWING
B	MOD 9452, NOTE RE FOR FUTURE ARRGT. OF TERMINAL BOLT ADDED. A.S.D. 11-3-94.
A	EARTHBONDS ADDED TO UNTRACKABLE. A60/62a

NOTES -
FOR ARRGT OF SHOEBEAM FIXING (OUTER AXLE) SEE DRG Nº 43591
(INNER AXLE) SEE DRG Nº 43590
" " " " POSITIVE SHOE GEAR. SEE DRG Nº 43594.
FOR REPLACEMENT POS ARC SPLASH BARRIER SEE DRG Nos 98099, 98098.

RASTER/VECTOR CAD DRAWING

A60/62 SURFACE STOCK.

ARRGT. OF POSITIVE SHOEGEAR TRIPCOCK GEAR & EARTH BONDS.
TYPES 'A' & 'D' MOTOR CARS & TRAILERS

SCALE. 3 INCHES TO 1 FOOT.

LONDON TRANSRORT EXECUTIVE.
CHIEF MECHL. ENGINEERS OFFICE.

DRG. No 43589.

DATE. 24-7-62. ZONE: 28.00

E D C B A

OFFICE. 407 FILING. 407

Transport for London
London Underground
MAYOR OF LONDON
UNCONTROLLED COPY
WILL NOT BE UPDATED
THIS DRAWING MAY NOT BE CURRENT AND IS SUBJECT TO AMENDMENT. THEREFORE DO NOT PROCURE OR MANUFACTURE ANY PART THERE OF, WITHOUT FIRST SEEKING VERIFICATION FROM THE RSE - ERM BEFORE USE

Filename: W:\user\Pln\dbs\data\Pln\Pln1\dms0674\43589.dgn
Printed: 10/09/02