

Material:
RIM moulded FR grade
medium density structural
polyurethane resin Elastagran
Duromer ref: UK-D-1443.

Finish:
All external surfaces to be
polyester painted semi-gloss
light metallic silver.

Notes:
5.0mm nom wall thickness
throughout unless otherwise
stated.
Nominal 1.0° draft angle
throughout.
All external faces to be free
from distortion, pitting and
bubbles.

Reference
JEDCo Product Designers
Drawing No.:
JED 389/101-2 rev C

A	09.05.07	FIRST ISSUE
	Date	Revision

**London Bus Services
Limited**


Infrastructure Development
172 Buckingham Palace Road
London SW1W 9TN
Telephone 020 7918 4939
Fax 020 7918 3567

© copyright TfL Original design for LBSL by
JEDCO Product Designers and Engineering

**METAL BUS STOP
STANDARD DRAWING**

Title
SOLAR CANOPY
SHORT MOULDING DETAIL

CALMS code		
© copyright TfL Drawn on behalf of LBSL by Trueform Engineering Ltd.		
Drawn	L.R.	Checked J.M.
Scale	NTS	Date 09.05.07
Drawing no. LBSL260/15/002		Rev A



- NOTES**
- A** THROUGH HOLE Ø 7.0
 - B** THROUGH HOLE Ø 5.0
 - C** THROUGH HOLE Ø 25.0
 - D** SLOTS 50.0 x 3.0 x 12.0 DEEP (UNDERCUTS)
 - E** THROUGH HOLE Ø 7.0
 - F** M4 THREADED INSERTS SET IN MAX Ø 18.0 TAPERED PILLARS

Remove all burrs and sharp edges unless otherwise stated
Tolerance unless otherwise stated to be ± 0.2mm