

POSITION OF THROUGH HOLES

**Finish:**


35 micron anodized Silver Satin finish to BS 1615 and BS 3967  
Anodic clamps to be attached to the internal webs only - and  
expressly not to any visible surfaces. Post to be free of  
rolling marks and surface imperfections .

**Note:**

Unless otherwise stated holes drilled through both sides of post .  
All holes to be de-bured inside and out.  
Avoid scratching and handle with care .  
For extrusion detail see Drg. No. LBSL 620/02/001

**Reference:**

Approximate finished weight - 11.4Kg.  
Remove all burrs and sharp edges unless otherwise stated  
Tolerance unless otherwise stated to be ± 0.5mm



B	10.05.07	New Border
A	12.02.99	FIRST ISSUE



**London Bus Services  
Limited**

Infrastructure Development  
172 Buckingham Palace Road  
London SW1W 9TN  
Telephone 020 7918 4939  
Fax 020 7918 3567

© copyright TfL Original design for LBSL by  
JEDCO Product Designers and Engineering

**METAL BUS STOP  
STANDARD DRAWING**

Title  
2M POST

CALMS code

© copyright TfL Drawn on behalf of LBSL by  
Trueform Engineering Ltd.

Drawn J.W. Checked J.M.

Scale 1:10 Date 12.02.99.

Drawing no. LBSL260/02/003 Rev B