



Engineering

Groundwater Level Monitoring

Document Number: CRL1-GCG-C2-RAN-CRG03-00002

Document History:

Revision:	Date:	Prepared by:	Checked by:	Authorised by:	Reason for Issue:
1.0	30/11/10	[REDACTED]	[REDACTED]	[REDACTED]	For Information Previously revision issued as 1D101-G0G00-00506 Rev H
1.9	25/11/11	[REDACTED]	[REDACTED]	[REDACTED]	Regular update. (Interim version)
2.0	21/12/2011	[REDACTED]	[REDACTED]	[REDACTED]	Regular update



This document contains proprietary information. No part of this document may be reproduced without prior written consent from the chief executive of Crossrail Ltd.

Contents

Executive Summary	3
1 Introduction	4
2 GROUNDWATER LEVEL MONITORING REQUIREMENTS.....	4
3 GEOLOGICAL SETTING.....	6
3.1 Regional Geology.....	6
3.2 Lithology	7
3.3 Crossrail Ground Investigations	10
3.4 Route Stratigraphy.....	10
4 HYDROGEOLOGY	12
4.1 General.....	12
4.2 Construction De-watering	13
4.3 Piezometric Data	14
4.4 Piezometric Profiles.....	20
4.5 Shallow Aquifer	23
4.6 Deep Aquifer.....	26
4.7 Tidal Variations	29
5 PLANNED GROUNDWATER MONITORING AND INTERPRETATION.....	32
6 REFERENCES.....	33

TABLES

FIGURES

APPENDIX A – Crossrail Piezometer – Digital Data

APPENDIX B – Piezometric groundwater levels of the Piezometers Installed during the 1992 Crossrail Ground Investigations

APPENDIX C – Summary of Problems Identified with Piezometers Installed during the 1992 Crossrail Ground Investigations

Executive Summary

The purpose of this report is to update, summarise and evaluate the available ground water level monitoring information across the Crossrail alignment. The report is produced periodically and the next update is planned for summer 2012. A separate report (CRL1-GCG-C2-RAN-CRG03-00001) presents information specifically for Crossrail construction dewatering activities.

Knowledge of groundwater pressures has already informed the design. For the construction phase, groundwater information is need for safe and good quality construction, to verify the design assumptions and to demonstrate and ensure that construction effects on third parties are; (i) as predicted, and (ii) suitably mitigated.

Data is presented in this report from Crossrail and third party piezometers for the shallow aquifer in the River Terrace Deposits, the intermediate aquifer in the Lambeth Group (where it exists, as it is impersistent) and the deep aquifer in the Thanet Sand/ Chalk.

This report provides the following information.

- A schedule of piezometers installed in Crossrail ground investigations and relevant third party piezometers, together with information on their reliability/ condition;
- The Crossrail digital groundwater database (in spreadsheet format);
- Time plots of piezometric levels measured in the post-2002 Crossrail piezometers;
- Piezometric profile plots presenting the groundwater pressure variation for each "route section". (The tunnelled alignment is divided into route sections so that each route section covers a short length of running tunnel or a major structure such as a station, portal, cross-over or shaft.)
- Contour plots of the ground water levels and ground water level changes in the shallow and deep aquifers;
- Summary plots of the measured tidal variation and its pattern over the Crossrail route;
- An analysis and commentary on the above data.

Conclusions

Since the start of Crossrail ground investigations in 1992, some 1300 piezometers have been installed to monitor the groundwater conditions. This information has been augmented by groundwater data from third parties. A detailed picture of the ground water conditions along and around the Crossrail tunnelled alignment is available and this has informed and continues to inform the project.

1 Introduction

The purpose of this report is to summarise the available groundwater level monitoring data for the Crossrail Alignment. Limited evaluation of the data is reported since a detailed interpretation of the data is included in the Geotechnical Sectional Interpretative Reports (GSIRs) (Refs. [1], [2], [6] and [7]), in other specific reports, namely "Monitoring of Construction De-watering" and "Monitoring of Groundwater Response to Tidal Variations" (Ref. [31] and [32]).

Data from piezometers installed during the site investigations carried out in the 1990's as well as the current, ongoing post-2002 investigations are presented. It is intended that the report will be updated periodically as further piezometers are installed and new readings are obtained from existing instruments. All of the available data is included in the report although some of it is considered unreliable.

Data from both the shallow aquifer in the River Terrace Deposits and the deep aquifer in the Thanet Sand/ Chalk is presented. For the deep aquifer, data on groundwater levels from the Environment Agency (Ref. [4]) has been used in combination with Crossrail and third party data to assess the variation in groundwater level both regionally and specifically along the Crossrail Alignment. A review of the piezometric profiles between the two aquifers is also included for all route sections between Royal Oak and Pudding Mill Lane and Plumstead Portals. These profiles highlight water pressures in the intermediate aquifer - intermittent zones where sand channels in the Lambeth Group have coalesced into a significant water bodies. Recommendations are made for future monitoring in line with the requirements of the project.

This report is based on Crossrail Alignment Revision "S" (Ref. [14]).

2 GROUNDWATER LEVEL MONITORING REQUIREMENTS

Monitoring of groundwater (piezometric) pressures is essential to determine the state of in situ effective stress in the ground and, as such, piezometric data are a key input into the design and construction of underground structures. The Crossrail project incorporates construction of stations, shafts, portals and tunnels, as summarised below.

Eight underground stations are proposed to be constructed for the Crossrail Alignment: Paddington; Bond Street; Tottenham Court Road; Farringdon; Liverpool Street; Whitechapel; Isle of Dogs and Woolwich. The existing at-grade Custom House Station on the North London Line will be redeveloped as part of Crossrail Alignment. The stations will typically be constructed using a combination of contiguous piling, sheet piling, diaphragm walling and sprayed concrete lining (SCL).

The Crossrail Alignment Rev. S includes 20 cross passages and 10 sumps between the running tunnels. These replace some of the fourteen shafts that were proposed to be constructed for the Crossrail Alignment Rev. M. Currently, only five shafts are still proposed to be constructed: Fisher Street; Stepney Green; Mile End Park; Eleanor Street and Limmo Peninsula. These

shafts will typically be constructed using a combination of underpinned precast concrete rings and SCL. The cross-passages will be constructed using SGI segments of SCL lining.

Five portals are being constructed for the Crossrail Alignment: Royal Oak; Pudding Mill Lane; Victoria Dock; North Woolwich; and Plumstead. The TBM launch/reception chambers and the walls for the cut and cover and retained cut sections of the portal will all generally be constructed using diaphragm walls. Sheet piles or bored piles will provide ground support to sections with a small retained height.

The bored tunnels linking the stations, shafts and portals along Crossrail Alignment will be constructed primarily using tunnel boring machines (TBMs) and lined with segmental precast concrete linings. SGI segments may be used at connections to stations and shafts and SCL may also be used in certain areas. Depending upon the type of tunnelling technique being used, groundwater pressures can present more or less of an issue to tunnel construction.

Knowledge of groundwater pressures for these structures is required to:

1. Identify granular strata with significant pore water pressures that may present an instability hazard to construction activities.
2. Estimate magnitudes of groundwater inflows during construction and the corresponding level of groundwater control expected to be needed during construction.
3. Determine the need for ground treatment to facilitate excavation, e.g. dewatering or grouting of high permeability strata.
4. Assess the effects of any dewatering settlements on adjacent buildings, services, structures and tunnels.
5. Determine appropriate construction technique(s), e.g. inclusion of cut-off walls or the use of caisson construction techniques.
6. Assess long-term settlements.
7. Assess the potential for base heave or structure flotation.
8. Form a baseline of natural groundwater fluctuations for a sufficient period prior to construction activities.
9. Assess the impact of construction de-watering proposal on local abstractors.
10. Design of the sub-surface structures, including the design of any tunnel or shaft linings.
11. Assess any changes to the local hydrogeological regime as a result of construction and the effects on neighbouring structures and potential contaminant transport.

12. Assess the effects of long-term changes in groundwater pressures and the design of the tunnels and structures to accommodate these changes.
13. Determine soil strength and stiffness (dependant upon the state of effective stress) for ground movement analyses.

3 GEOLOGICAL SETTING

3.1 Regional Geology

The Crossrail alignment between Royal Oak and Pudding Mill Lane and Plumstead Portals is covered by the following British Geological Survey 1:50 000 maps: Sheet 256 (North London, 1994), Sheet 257 (Romford, 1996), and sheet 271 (Dartford, 1998). The relevant sections of these maps are reproduced as Figure 3.1.1. The parts of the alignment covered by the three Geotechnical Sectional Interpretative Reports are indicated on the figure. A geological long section for the whole alignment is reproduced as Figure 3.1.2.

The generalised geological succession in the London Basin is outlined in Table 1. The floor of the basin comprises Cretaceous Chalk, overlain successively by Palaeogene deposits: Thanet Sand Formation, Lambeth Group, Harwich Formation and London Clay Formation. Near surface the more recent Quaternary deposits comprise River Terrace Deposits, Langley Silt and Alluvium. A variable thickness of Made Ground is to be expected from the surface within the urban environment along the route.

Figures 3.1.1 and 3.1.2 show that the full sequence of strata (excepting the impersistent Harwich Formation and recent Holocene deposits) typical of Central London are present over virtually all of the area covered by GSIR 1/2 (Ref. [1] and [2]) between Royal Oak Portal and Liverpool Street Station. River Terrace Deposits are absent in the extreme west around Royal Oak Portal and Paddington Station. Alluvium is only mapped as present associated with major tributaries of the Thames (including the Rivers Westbourne, Tyburn, Fleet and Walbrook), where RTD may be locally absent. Localised deposit of Langley Silt are mapped around Paddington, Hyde Park, south of Fisher Street Shaft and in the area of Farringdon and Liverpool Street. Harwich Formation is thin and impersistent in central London. It has only been identified intermittently around Tottenham Court Road, Bond Street Station and Liverpool Street Station areas. A significant zone of faulting / folding has been identified in the Farringdon area (Ref. [1] and [2]). There is also some evidence of faulting in the Lambeth Group at the east end of Tottenham Court Road Station (Refs. [35], [36] & [45]) and at Bond Street Station (Ref [50] and [51]).

In the area covered by GSIR 3 (Ref. [6]), between Liverpool Street Station and Pudding Mill Lane Portal and west of Isle of Dogs Station, the full sequence of strata is also present except in the eastern part of this area, along the Isle of Dogs branch, where the alignment crosses the London Clay subcrop east of Limehouse at EB Chainage 13000. London Clay is present throughout the Pudding Mill Lane branch but the end of the portal / ramp structure is within about 100m of the mapped subcrop of the London Clay. Harwich Formation was identified in approximately 51% of boreholes which penetrated through London Clay. The Lambeth Group contains sand channels which coalesce into continuous or semi-continuous bodies over much

of the GSIR3 area, and constitute an intermittent intermediate aquifer between the deep and shallow aquifers. Alluvium can be expected at Pudding Mill Lane Portal in the River Lea valley and close to the Isle of Dogs Station in the Thames flood plain, and locally in other areas associated with minor water courses.

The geology is more complex in the area covered by GSIR 4 (Ref. [7]) between Isle of Dogs Station and Plumstead Portal. At the Isle of Dogs Station, London Clay is absent on the western side and re-appears at EB Chainage 13750, where the subcrop crosses the Isle of Dogs Station footprint (Ref. [7] & [21]). Immediately to the east, the alignment between Custom House Station and the North Woolwich Portal, the London Clay Formation, the Lambeth Group and the Thanet Sand Formation successively subcrop below the River Terrace Deposits. Harwich Formation was identified in 94% of the boreholes which penetrated through London Clay. Similarly, the Lambeth Group contains sand channels which have coalesced into a continuous Sand Unit over this stretch of the alignment, and which sub-crop beneath the RTD at Connaught Tunnel.

At the North Woolwich Portal and below the River Thames, River Terrace Deposits directly overlie Chalk. A filled-basin/scour feature has been identified in the Chalk below the River. This too could be fault controlled. To the south of the River, the alignment runs within the mapped limit of Head Deposits. River Terrace Deposits, where present, directly overlie Thanet Sand or Lambeth Group. Lambeth Group material is only encountered locally along the alignment, infilling an apparent erosion feature in the surface of the Thanet Sand.

Alluvium can be expected to overlie the River Terrace Deposits over almost all of the area covered by GSIR 4, with the possible exception of the area south of the River Thames where head deposits are indicated on Figure 3.1.1. The material mapped as Head Deposits was recovered in Package 10 & 20 ground investigation boreholes and careful logging has indicated that it is in-situ weathered Thanet Sand. Discussion on the head deposit and in-situ Thanet Sand is given in GSIR 4 (Ref. [7]).

Faults have been identified at Isle of Dogs, Limmo Peninsula, North Woolwich (associated with the Greenwich fault zone) and Woolwich Station. Further discussion on faulting across the Crossrail alignment is given in GSIR4 and in the tunnel fault crossings (Ref. [7] and [35], respectively).

3.2 Lithology

Chalk is a soft, very pure white limestone formed from the skeletal remains of submicroscopic algae. Two features commonly found in Chalk are flints and marl seams. Flint is a microcrystalline silica rock that occurs usually as black nodules or as tabular bands or sheets. Flints represent very strong, brittle inclusions in the comparatively weak host Chalk matrix. Marl seams are horizons with increased concentrations of clay. As a result of its nature, the Chalk is a low storage high transmissivity aquifer with dual porosity. The majority of the flow occurs in the fractures, whereas the most of the storage is in the matrix, with water slowly released to the fractures when ground water levels fall (e.g. ref. [5]).

The Thanet Sand Formation is the oldest Palaeogene deposit and is characterised as a homogeneous, grey, silty, fine to medium sand. At the base, the Bullhead Beds, a thin conglomerate of rounded flint gravels and larger nodular flints in a matrix of greenish grey to dark grey, glauconitic, sandy clay lies unconformably on the Chalk.

Much work has been done in recent years in examining the stratigraphy and engineering characteristics of the Lambeth Group (formerly known as Woolwich and Reading Beds) as described by Page and Skipper (Ref. [18]) and Hight et al. in CIRIA Funders' Report CP/83 (Ref. [10]). This work has resulted in some changes to the nomenclature of the Lambeth Group units as summarised below:

Unit	Former Classification	Formation
Upper Shelly Beds (USB)	Upper Shelly Clay (USC)	Woolwich
Upper Mottled Beds (UMB)	Upper Mottled Clay (UMC)	Reading
Laminated Beds (LTB)	Laminated Sands and Silts (LSS)	Woolwich
Lower Shelly Beds (LSB)	Lower Shelly Clay (LSC)	Woolwich
Lower Mottled Beds (LMB)	Lower Mottled Clay (LMC)	Reading
Upnor Formation (UF)	Pebble Bed and Glauconitic Sand (PB and GS)	Upnor

- **Upper Shelly Beds:** comprising hard cemented shell conquinas, leaf beds and laminated dark grey shelly clays.
- **Upper Mottled Beds:** comprising predominantly stiff to hard fissured and mottled multicoloured silty clays.
- **Laminated Beds:** comprising very stiff light grey finely laminated clay-silt and silt-sand with occasional shell beds.
- **Lower Shelly Beds:** comprising very stiff mid-dark grey laminated clay, sandy clay and shells.
- **Lower Mottled Beds:** comprising intermittently a duricrust at the top (details of which is given below) and predominantly hard fissured mottled multicoloured sandy clays, occasionally silty sands or pebbles.
- **Upnor Formation:** comprises pebbles and flint gravel in sandy matrix, laminated grey clay and brown to grey sand, glauconitic fine to coarse sand with occasional black pebbles and shells.

A duricrust, generally consisting of a hardened accumulation of calcrete, silcretes (mainly in the northwest region of the London Basin) or ferricretes (mainly in the southeast region of the London Basin) may have formed at or close to the top of the Lower Mottled Beds. This duricrust is commonly encountered at or just below the Mid Lambeth Hiatus, which represents the transition from terrestrial to marine deposition identified by the boundary between the LMB and the overlying LSB.

Within the Lambeth Group, in the area covered by GSIR 3 (Ref. [6]), sand filled channels can be expected stratigraphically at the top of, or within the Upper Mottled Beds and the Laminated Beds. Sand Channels have also been found within the Lower Mottled Bed. The sand is characterised as clean or pyritic quartz fine to medium sand. The channels are laterally extensive and they can be up to about 2m in depth and up to about 5m wide, possibly in hydraulic continuity. In GSIR4 area, it has been found that the Sand Channels have coalesced into a previously unmapped sand layer - this is referred to as the Lambeth Group Sand Unit. The sand unit occurs beneath the Harwich Formation at the top of Lambeth Group overlying either the Upper Mottled Beds, which it commonly replaces or erodes, or the Laminated Beds. With regard to the Crossrail alignment this unit is persistent between EB Chainage 14450 - 17700 (Route Sections J to L) (see GISR4, Ref. [7]). Sand Channels have also been found in GSIR1&2 areas, e.g. Bond Street Station (thicker than 6.6m in places) and Farringdon Station.

The variation in the characteristics of the Lambeth Group lithologies results from the different depositional environments in which they were laid down and the subsequent post-depositional changes. The Upnor and Woolwich Formations were deposited in shallow marine or estuarine waters while the Reading Formation was deposited in alluvial or supratidal environments. The cycles of regression and transgression of sea level resulted in the heterogeneity of the deposits and in their high vertical and lateral variability.

The Harwich Formation corresponds to the former Division A1 of the London Clay Formation and is divided into three units, although all units may or may not be present at any given location:

- **Swanscombe Member:** comprising glauconitic sandy clay with common thick-shelled molluscs.
- **Oldhaven Member:** comprising fine glauconitic sand with shells and, at the base, a bed of large black, rounded flint pebbles which may be thick and shelly.
- **Blackheath Beds:** the oldest unit comprising rounded to subrounded flint pebbles with a limited matrix of fine to coarse sand or clay.

London Clay consists of mainly dark bluish to brownish grey clay, containing variable amounts of fine-grained sand and silt. The clay generally weathers to a chocolate brown colour. London Clay is relatively homogeneous in lithology in comparison with, for example, the Lambeth Group, but there are distinct vertical lithological changes which are persistent regionally in the London area. The London Clay Formation was divided by King (Ref. [11]) into the successive lithological 'Divisions' A, B, C, D and E. For the Crossrail underground route alignment, only the lower part of the London Clay Formation is present, comprising Divisions A, B and C. (Division C is only present between Royal Oak Portal and Hyde Park.) Division A1 has been reclassified as part of the Harwich Formation, as detailed above.

The River Terrace Deposits in the London area were formed during the colder climatic periods of the Pleistocene. They consist of gravel sheets that were formed in response to heavy seasonal snow-melt run-off. This run-off formed a series of braided channels that meandered and interlinked across a wide flood plain. The material deposited is a well-graded mixture of sand and gravel, occasionally with cobbles where stream flow was intense, and occasionally with silt or silty sand layers formed in slacker water.

Alluvium comprises river deposits (mainly sand, silt and clay) laid down in the recent Holocene period. Langley Silt, where present, overlies the River Terrace Deposits and was formed in the

Devensian Period, either as a loess deposit or as a fluvial overbank loam deposit. Langley Silt was formerly known as “Brickearth” and comprises grey, buff, orange or brown coloured, sandy silt and clayey silt with occasional gravel bands.

It was mined extensively for the manufacture of bricks; hence the remaining deposits can be discontinuous.

Made Ground is the most variable of all the strata. Its nature and thickness depends on previous developments and land uses that have taken place at a particular location including the cycles of reconstruction. Made Ground normally contains a high proportion of locally excavated soils, demolition rubble and previous building foundations, but also could contain contaminants from industrial processes and active service pipes and utilities.

Further details of the lithology along the Crossrail alignment can be found in the Geotechnical Interpretative Reports (Ref. [1], [2], [6] and [7]).

3.3 Crossrail Ground Investigations

Ground investigations were carried out between 1992 and 1996 for the original Crossrail scheme between Royal Oak Portal and Liverpool Street Station. Additional ground investigations for the extended Crossrail Alignment (post-2002 investigations) have been carried out for the new stretch of the alignment to the east of Liverpool Street Station towards Abbey Wood, south of the River Thames. Several more ground investigations have also been undertaken to provide up-to-date information throughout the tunnelled alignment, to revisit specific locations where changes in the alignment occurred (e.g. at cross passage locations) or to investigate specific issues identified during design development.

The sequence of investigations is summarised in Table 2 together with the borehole prefixes relevant to each phase/package of work. The extent and timing of the various phases have been determined primarily by financial constraints. The works included in each phase were established in liaison with the project designers and have taken into consideration the information obtained from earlier ground investigations as well as changes in vertical and horizontal tunnel alignments (Alignment Revisions “H” to “S”).

In addition, further ground investigation may be carried out by the appointed Contractor to investigate specific issues or to provide additional information for design purposes (e.g. for the design of ground treatment measures).

3.4 Route Stratigraphy

Figure 3.1.2 illustrates a schematic of the geological profile, the piezometric levels of the deep aquifer and vertical piezometric profiles for the Crossrail Alignment (Royal Oak Portal to Plumstead and Pudding Mill Lane Portals). Piezometric levels are given for August 2008 (baseline before start of Crossrail de-watering) and August 2011 (the latest data, which also reflects the effect of IoD de-watering). Further details of the de-watering are given in Section 4.2.1.2. The piezometric profiles along the alignment are discussed in Section 4.4.

Between Royal Oak Portal and Fisher Street Shaft, the station and portal structures will be constructed primarily in London Clay and the overlying superficial deposits. The lower levels of Bond Street Station, Tottenham Court Road Station and Fisher Street shaft are expected to just penetrate the Upper Mottled Beds of the Lambeth Group. Over these route sections, the running tunnels and cross-passages will be constructed in London Clay. Between Fisher Street

Shaft and Farringdon Station, increased penetration into the Lambeth Group is expected with the running tunnels and cross-passages being constructed in Lambeth Group. Farringdon Station is located within a faulted zone. Between Farringdon and Liverpool Street Stations the running tunnels will be constructed in a mix of London Clay and Lambeth Group soils; the lower levels of Liverpool Street Station are expected to just penetrate into the Lambeth Group.

To the east of Liverpool Street Station as far as EB Chainage 9600 the running tunnels and cross-passages continue in a mix of London Clay and Lambeth Group soils. Further to the east, the alignment rises above the London Clay / Lambeth Group interface such that Whitechapel Station is expected to be constructed almost entirely in London Clay. The running tunnel vertical alignments diverge east of Whitechapel Station towards the junction at Stepney Green: the shallower eastbound tunnel is within London Clay and the deeper westbound tunnel enters the Lambeth Group and is partly within this stratum at Stepney Green.

As the London Clay thins towards the south and east, the running tunnels and structures associated with the Isle of Dogs branch of Crossrail Alignment will penetrate further into the Lambeth Group and will enter the Thanet Sand Formation (EB Chainage 12100). Along this part of alignment the running tunnels and cross-passages are generally in mixed face Lambeth Group / Thanet Sand, occasionally fully within the Thanet Sand, through the Isle of Dogs, with the lower part of Isle of Dogs Station being constructed in the Thanet Sand Formation. East of Isle of Dogs the London Clay thickness increases rapidly due to the faulting system identified at Limmo Peninsula and the tunnels are predominantly in London Clay between Limmo shaft and Victoria Dock Portal. Exceptions are a short section where up to a half face of Lambeth Group will be encountered and a section close to the portal where River Terrace Deposits locally thicken.

The existing Connaught tunnel and portal structures encompasses the mapped subcrops of the London Clay Formation and the Lambeth Group, although the tunnels are predominantly located within the River Terrace Deposits and overlying superficial deposits.

From North Woolwich to Woolwich Station, construction will primarily be in Chalk. Thanet Sand Formation and River Terrace Deposits will be encountered at the portal and station along this section of the alignment. The cross-passages will be in chalk. To the east of Woolwich station the running tunnel and cross-passages will be constructed primarily in Chalk.

For the Pudding Mill Lane branch of the alignment, running north-east of Stepney Green junction, the shallower eastbound tunnel remains in London Clay until prior to Eleanor Street shaft, where it enters the Lambeth Group soils. The deeper westbound runs in a mix of London Clay and Lambeth Group soils and then joins the eastbound before Eleanor Street shaft. Further east penetration into the Lambeth Group soils increases as the thickness of the London Clay reduces. River Terrace Deposits and Alluvium will be encountered close to and at Pudding Mill Lane Portal.

4 HYDROGEOLOGY

4.1 General

The hydrogeological regime of the London Basin incorporates a deep aquifer comprised of the Chalk and lower Palaeogene deposits of the Thames Group (i.e. the Thanet Sand Formation and the Upnor Formation (Lambeth Group)). There is also a variable shallow aquifer within the more recent Pleistocene River Terrace Deposits. In Central London, the deep and shallow aquifers are separated by the low permeability London Clay and low permeability units of the Lambeth Group. As these strata thin towards the margins of the Basin, the deep aquifer becomes linked with the shallow aquifer. Localised shallow perched water tables may also be present above low permeability layers within the Alluvium, Langley Silt and Made Ground at some locations.

Groundwater abstraction from the deep aquifer during the last two centuries has led to significant lowering of the piezometric pressure in Central London resulting in underdrained piezometric profiles where pore pressures within the London Clay and Lambeth Group are generally lower than hydrostatic from the water level in the shallow aquifer. Groundwater abstraction peaked in the 1960s, by which time the groundwater level in the deep aquifer had dropped to 88m below sea level (12m ATD) (Ref. [5]). The subsequent reduction in abstraction resulted in a gradual rise of the groundwater levels in the deep aquifer, as described by Simpson et al (Ref. [20]).

Rising groundwater levels in the deep aquifer would change the piezometric profiles in the London Clay, Lambeth Group, Thanet Sand Formation and Chalk. As a consequence, buried structures may be subjected to an increase in pore water pressures leading to a reduction in stability and/or deformation of the structure (Ref. [30]).

GARDIT (General Aquifer, Research, Development and Investigation Team) was established in 1992 as a group of parties interested in controlling groundwater in the deep aquifer and included Thames Water, London Underground and the Environment Agency. The objective of the five phase GARDIT strategy is to increase abstractions 'to control groundwater level in the Chalk aquifer under Central London in order to maintain the integrity of underground structures and foundations in the London Clay (Ref. [5]). This strategy was fully implemented by about 2004 with most of the key abstractions having been developed (ref. [5]) and the water levels well controlled. However, the issue of groundwater level control is ongoing and the Environment Agency remains responsible for monitoring groundwater levels and management of the abstraction licensing. More recently, the increasing use of open loop Ground Heat Source Pumps (GHSP) has added a new variable to factors affecting the water levels in the deep aquifer. Schemes usually take several years to progress from proposal through investigation to implementation. In addition, water usage is seasonal. Further discussion on the deep aquifer is given in Section 4.6.

Apart from the upper and lower aquifers, other potential groundwater bearing strata of relevance to Crossrail alignment are the Harwich Formation as well as Sand Channels and other granular strata present within the Lambeth Group. In some locations these strata are laterally extensive and have a significantly high permeability. Where separate upper and lower aquifers exist, these strata are not in hydraulic continuity with either the deep or the shallow aquifer and so

comprise an intermediate aquifer. They can lead to substantial seepage flows into excavations. Measured pore water pressures within the intermediate aquifer are consistent with the surrounding soils (see Section 4.4).

4.2 Construction De-watering

De-watering activities have been planned at several sites along the Crossrail alignment to correspond with stations, portals, shafts and cross-passages depending on the ground conditions, groundwater conditions, geometry and proposed construction method. Table 3 presents an outline programme for the Crossrail works that will involve major de-watering schemes during construction (based on Ref. [54]). Where construction extends close to or into the Lambeth Group some de-pressurisation of sand horizons within the Lambeth Group may be required.

Further details on the de-watering scheme associated with the Crossrail alignment are described in Ref. [33].

To date, de-watering has commenced only at Isle of Dogs (IoD) for the construction of the IoD Station (Ref. [31] & [33]).

4.2.1 Isle of Dogs

4.2.1.1 Background

Several cycles of de-watering have been undertaken at the Isle of Dogs in order to allow the construction of different structures at/near to Canary Wharf. The first phase of de-watering of the deep aquifer took place between July 1994 and April 1997 to allow the construction of Canary Wharf Station for the Jubilee Line Extension. During this phase 10 abstraction wells were installed around Canary Wharf. However, only 6 wells were pumped achieving a stabilised groundwater level of about 74m ATD. Following the completion of construction, de-watering ceased and the piezometric level returned to the previous state between 90 and 94m ATD (Ref. [22] and [26]).

A second phase of de-watering of deep and shallow aquifer was undertaken from late 1998 to 2001 for the development of the Dockland Square and Heron Quays sites. In particular, the deep aquifer de-watering scheme was designed to lower the groundwater level below 72m ATD in order to allow the construction of foundation piles under dry conditions. However, the deep aquifer was lowered to a minimum level of 70m ATD (Ref. [23] and [24]). The de-watering scheme exhibited effects several kilometres to the east and west of the Canary Wharf underlining the effects of regional drawdown (Ref. [25]).

The third phase of de-watering was carried out between 2001 and 2005 for construction at Blackwall Place. The aim was to reduce the water level of the deep aquifer to 77m ATD (Ref. [23] and [24]), which was achieved in 2005.

The fourth phase of de-watering of deep and shallow aquifer was undertaken west of Canary Wharf for the Riverside South project. For the de-watering of the shallow aquifer, there was in

place a network of 17 boreholes, to achieve a groundwater level between 99-95m ATD. This abstraction activity commenced in April/May 2007. In addition, de-watering of the deep aquifer was carried out between January and July 2008, achieving a level in the deep aquifer of 74m ATD (Ref. [28]). The effects of these pumping activities in the shallow and deep aquifer have been recorded at a maximum distance of approximately 680m north and 1000m east from the abstraction site, respectively (see Section 4.3.5.1).

De-watering at Isle of Dogs has highlighted a difference in the deep aquifer's response between the west and east side of West India Dock (North); with the eastern end experiencing less drawdown and a faster recharge rate. This is likely to be related to the presence of a scour hollow at the eastern end of Isle of Dogs providing a means for easier/direct recharge from the River Thames/shallow aquifer. In addition, a fault through the Thanet Sand and Chalk Formation at West India Dock (North) appears to serve as a partial barrier to flow within the aquifer which decelerates recharge in the western block of the aquifer (Ref. [21] and [23]). Figure 3.1.2 shows this fault schematically, near EB Chainage 14300. Groundwater monitoring data showing the variation in response to the dewatering scheme are presented and discussed in Section 4.3.5.1 and 4.4.

4.2.1.2 Crossrail De-watering at Isle of Dogs

De-watering activities in preparation for the construction of the Isle of Dogs Station commenced in early August 2008 with the installation of fourteen deep wells screened in the Chalk. The target was to lower the groundwater level in the deep aquifer to 63m ATD and it was achieved in December 2008. Since then, the rate of pumping has been reduced to "maintenance" levels with 12 to 14 wells in operation around West India Dock (North).

Groundwater monitoring data showing the variation in the deep aquifer level induced by this de-watering activity are presented and discussed in details in the relevant Construction De-watering report (Ref. [31]). Figure 3.1.2 summarises the current situation which shows de-watering drawdown extending west towards Stepney Green and east as far as Connaught Tunnel, with local recharge at scour hollows near EB Chainage 14300 and 15900.

4.3 **Piezometric Data**

4.3.1 General

During the course of the ground investigations that have been carried out as part of the Crossrail project, 1314 piezometers have been installed in boreholes along the route alignment. This total comprises 233 piezometers from the 1992 ground investigations and 1081 piezometers from the post-2002 ground investigations. In addition, arrangements have been made by CRL to collate data from additional 81 installation owned by third parties (i.e. LUL and Canary Wharf Contractors (Crossrail)).

4.3.2 1992 Crossrail Piezometers

Details of the piezometers installed during the 1992 ground investigations are given in Appendix A. The piezometers that were installed during these ground investigations included pneumatic piezometers, standpipes and standpipe piezometers. In July 1997, (when monitoring was discontinued) only 64 of these piezometers were functioning, with the remainder either broken/destroyed or of unknown condition. More recently, surveys to identify any remaining functional standpipes / standpipe piezometers were undertaken by Norwest Holst Soil Engineering Ltd (NHSEL) in 2004 (Ref. [16]) and by GCG in 2006. It is considered that pneumatic piezometers are unlikely to be functional or reliable due to damage to the valves, blockages in the tubing or de-saturation of filters and no attempt has been made to locate these instruments.

Only 7 standpipes / standpipe piezometers were found to be fully functional after the completion of the first phase of remedial works (refer to Ref. [40] for more details). A further 2¹ installations were identified which may be recoverable. The remediation works for the pre-2000 piezometers are currently completed. Two installations are still under observation (refer to Ref. [40] for more details). Another round of remediation/ maintenance work might be carried out soon. On this basis, the maximum number of functional piezometers could become 28, if all remedial works are successful - i.e. approximately 2% of the instruments installed. Common reasons for piezometers being non-functional were the inability to locate the installation, normally as a result of resurfacing of the roadway or redevelopment of the site, or damage/blockage to the piezometer installation. An update summary of the problems identified with the 1992 piezometers is given in Appendix C.

Plots of the recorded piezometric groundwater levels against time for the 1992 piezometers are reported in Appendix B. The data are grouped according to the alignment sections defined in the 1992 Geotechnical Interpretative Reports (Ref. [1] & [2]) and shown in Figure 3.1.2. The raw data for these plots are tabulated in Appendix A.

4.3.3 Post-2002 Crossrail Piezometers

Details of the piezometers installed during the post-2002 ground investigations are given in Appendix A. The piezometers included standpipe, gas standpipe, Casagrande standpipe, PiezoPress and vibrating wire piezometers. Two Solexperts Multi-Port Sampling (MPS) systems were installed at Whitechapel as part of the Package 1 ground investigations – additional details

¹ An additional 17 installation were noted as “not located”. A further attempt may be made to find these piezometers and it may be that some of them may be recoverable.

of these installations are given in Ref. [6] and [9]. In addition, five multi-level piezometer systems have been installed at Stepney Green. These comprise three multi-level grouted in vibrating wire systems, two Waterra continuous multi-channel tube (CMT) systems and a Solexperts multi-port sampling system (MPSS). Details of these installations carried out as part of Package 12 and Package 13-VO2 are given in Refs.[8], [37], [38], [39] and [41]. Following the successful trial at Stepney Green (ref [8]), the Waterra CMT system has been rolled out as follows: two CMT-7 boreholes have been installed at Tottenham Court Road as part of Package 16 ground investigation, four CMT-7 and one CMT-3 boreholes at Farringdon as part of Package 13 and nine CMT-7 boreholes as part of Package 16A ground investigation between Paddington and Tottenham Court Road. Several vibrating wire piezometers have been installed at Isle of Dog. However, a number of the piezometers that have been installed are either no longer functioning or are deemed unreliable, as indicated by the colour coding in Appendix A. The first phase of remediation/ maintenance works has been completed and reported. The second phase is currently in progress. A summary of the piezometers scheduled for remediation, and proposed/ implemented remedial actions are given in Ref. [34], [40] & [46]. Further details and an update on progress to date are given in Section 4.3.4

The piezometers discussed above are designed to measure the groundwater conditions along the alignment. Additional information on groundwater conditions away from the Crossrail alignment can be obtained from 3rd party piezometers and Environmental Agency data, as well as planned off-alignment Crossrail sentinel wells (Package 27B, Ref. [48]). These off-alignment piezometers are useful for establishing groundwater drawdown cones from construction dewatering activities.

Figures 4.3.1 to 4.3.31 are plots of the recorded piezometric groundwater levels against time for the post-2002 piezometers grouped by Route Section (Table 4). The digital data for these plots is presented in the Crossrail Groundwater Database, in Appendix A.

4.3.4 Piezometer remediation

Piezometers require maintenance after installation for a number of reasons. The main problems encountered with the Crossrail piezometers are:

- Boreholes not located - likely to have been tarmaced over during road resurfacing, covered by grass and/or fly tipping, or in areas that become redeveloped/ paved since the piezometer was installed.
- Borehole headworks covers that could not be opened – due to stripped screw-tops and/or rusted screws
- Borehole headworks flooded – most typically due to blockage of the headworks filter/ drainage system
- Borehole headworks flooded – due to sunken headworks or headworks that were set low from the onset, relative to the surrounding ground level. This leads to ponding of water in the headworks and inflow of surface runoff into standpipe piezometers in an erratic manner that renders the measured data unreliable.

- Piezometer standpipes that are set low in the headworks, below the headworks drainage outlet. As a result, when surface run-off enters the headworks, the piezometer standpipe gets flooded first, before the water level reaches the headworks drainage outlet.
- Boreholes installations blocked or reporting high and variable water level (e.g. due to a possible inflow of surface water into the piezometer standpipe).
- Borehole reporting high water levels in comparison with most other installations in the surroundings

On the basis of the pattern of problems observed above, a first phase of remediation/ investigation work was undertaken between February 2009 and March 2010. The scope of this phase of remediation work included 121 piezometers (see Ref. [34] & [46]). Of these 71 installations were successfully remediated and brought back to working conditions, whereas 38 were founded to have been destroyed or were abandoned as not serviceable. A remaining 12 installations are still under remediation/ investigation & observation. The next phase of piezometer remediation work is currently on going; further details can be found in Ref. [40].

4.3.5 Down-hole piezometric data loggers

In standpipe piezometers it was possible to install a submersible piezometric data logger known as a “Diver”. The Diver is a self-contained instrument manufactured by Van Essen Instruments comprising a sealed stainless steel cylinder housing a pressure sensor, temperature sensor, solid state memory and a long-life battery (Ref. [3]). An optical link is used to both program and download data from the Diver. The Divers record absolute pressure which needs to be corrected for changes in barometric pressure; the latter being readily achieved using a similar type of data logged instrument referred to as a “BaroDiver”, which measures atmospheric pressure at the ground surface.

Divers were installed in various piezometer installations for the following purposes:

- Continuous monitoring to evaluate groundwater response to tidal variation
- Continuous monitoring of the de-watering drawdown
- Investigate anomalous behaviour (e.g. high or unexpectedly variable groundwater levels, water level recovery after cleaning/ flushing out problematic piezometers etc.)
- Continuous monitoring during pumping tests carried out as part of CRL ground investigations
- Permeability testing in low permeability soil

Section 4.3.5.1 gives a brief commentary on the diver data that record particular groundwater features (such as effects of third party pumping activities). In addition, separate reports have been produced to present and discuss the specific aspect investigated using diver data. In particular, the tidal report presents detailed analysis of the influence of tidal variations (Ref. [32]). The Monitoring of Construction De-watering reports (Ref. [31]) provide a detailed commentary on the diver monitoring data, which show the effect of current Crossrail de-watering for the construction of IoD station (Section 4.2.1.2). Diver data obtained during the piezometer remediation/ investigation work, in relation to the investigation of anomalous piezometers, are presented and interpreted in Ref. [40]. Analyses of relevant pumping test diver data and diver data obtained during permeability testing will be conducted, in order to obtain information on the mass permeability and hydraulic interconnectivity for Geotechnical Interpretative Reports that are in preparation. Finally, the permeability report presents the diver data obtained during permeability testing (Ref. [47]).

4.3.5.1 Commentary on data

All diver data have been included in the groundwater data base (Appendix A) as daily average values² and have been presented in Figures 4.3.1 to 4.3.31 together with the manual dipped measurements. Separately, all available diver data have been checked for tidal variation response, as discussed in Section 4.7 and reported in tidal report (Ref. [32]). A detailed review of the diver data collected up to 2009 is given in the previous revision of this report, Ref. [55]. However, the main findings have been reported in points below:

- The diver data collected for the shallow aquifer within the Isle of Dogs demonstrates the effect of the pumping that occurred on the west side of Westferry Road between April and August 2007. The data shows that this pumping activity had a zone of influence greater than 960m and that it affected not only on the River Terrace Deposits but also the underlying strata, such as the LSB. This pumping relates to the River South project, see Section 4.2.1.
- The data collected from piezometers located in the deep aquifer within the Isle of Dogs before 2008, shows a rise in the groundwater level of about 2 and 2.5m over a period of 4 and 10 months (refer to Figure 4.3.33 for borehole locations). This behaviour is believed to be due to the recovery in the deep aquifer following cessation of the third

² For completeness, all pumping test data, at the monitoring frequency utilised during the pumping tests, are also included in Appendix A as separate spreadsheets. This includes flow rate measurements.

phase of dewatering for construction at Blackwall Place (Section 4.2.1 refers). All deep piezometers located within the Isle of Dogs exhibited similar behaviour. Figure 4.3.34 presents the rate of recharge (m/month) recorded in 2007-08 in each installation against the distance from Cartier Circle, which has been assessed as the centre point of the pumping wells active during the third phase of Blackwall Place dewatering. A different behaviour is exhibited by CH35P, CH1R and CH2R: this is believed to be due to the presence of a fault running through West India Dock (Ref. [21]), which acts as a barrier to flow in the deep aquifer. The combination of the pumping activity and the fault emphasizes the difference in groundwater level between the western and eastern side of Isle of Dogs (refer also to Section 4.4)

- The data collected for the deep aquifer within the Isle of Dogs in 2008 show the effect of the fourth dewatering scheme carried out between January and July 2008 for the River South project (see Section 4.2.1). Looking at the responses of the piezometers within Isle of Dogs to the abstraction activity (Figure 4.3.33), the data shows that the rate of drawdown is inversely proportional to the distance from the pumping site, see Figure 4.3.35. Envelopes indicating the lower and upper bounds of the data are presented on Figure 4.3.34. Boreholes on the northwest of the site lie close to the lower bound whereas those on the eastern side are close to the upper bound. This behaviour could be related to the difference in groundwater levels before pumping, which increased to the east. It could also be related to the fault at the Isle of Dogs. If indeed the fault is serving as a barrier to flow, then piezometers between the fault and the pumping zone would experience rapid draw down as recharge from the far field on the east side would be inhibited by the fault. On Figure 4.3.34 the response of CH1R, CH35P and CH2R has been highlighted; these instruments are to the east but do not lie on the upper bound line as expected. This is likely to be due to the combination of the effects of the fault through the West India Dock (Ref. [21]) on the flow and of the recharging of the deep aquifer, which is controlled from the east.
- Figure 4.3.36 presents a summary and comparison of the entire diver data collected for the shallow aquifer within the Isle of Dogs in Package 15A boreholes. Note that instruments in boreholes IOD100, IOD102 and IOD104 are located below the West India
- Dock. The data exhibit the same behaviour in all piezometers and show a groundwater level generally around 100.5m ATD, confirming that the piezometers are in hydraulic continuity. However, IOD102 exhibits the same pattern as the others but shows a higher groundwater level of around 101.3m ATD. This could be due to infiltration/leakage from the overlying dock water into the piezometer or due to a localised high water level. However, it has not been possible to further investigate the reliability of this piezometer as it was destroyed during the Isle of Dogs construction works. Figure 4.3.46 also presents dock water levels (Ref. [29]). The difference between the dock water level (average level 104.25m ATD) and the groundwater level at IOD100, IOD102 and IOD104 (located below the West India Dock) is believed to be due to the cut off created by the Dock Sediment. Therefore, at this location the shallow aquifer is confined by the overlying Dock Sediment, with a hydraulic head of some 3m across the dock silt layer. This appears to be confirmed by the data recorded during the period in which draining of

the Isle of Dog station box was carried out. There is no significant response of pore water pressure in the RTD to the lowering of the dock water level (see Figure 4.3.36). However, a rise in the upper aquifer water level has been observed in April 2009 and July 2010. The former event is believed to be due to the cessation of the shallow aquifer activity at Riverside South project (refer to Section 4.2.1.1 for more details). It is not clear what the cause of the second rise in July 2010. However, it should be noted that the water levels are currently decreasing.

4.4 Piezometric Profiles

Profiles showing the variation in piezometric pressure with elevation have been generated using the data from the 1992 and post-2002 piezometers. Also shown are the best-judgement lines fitted to data collected up to August 2011. Where a piezometer is no longer working, or where a piezometer is believed to be reporting unreliable pressures, these profiles have been generated using the last reliable reading from that instrument. Some of the post-2002 piezometers are still stabilising or have preliminary information that needs to be verified. Where appropriate, this has been noted on the profiles. Figure 3.1.2 presents the profiles plotted on the geological long section for illustrative purpose only, while Figures 4.4.1 to 4.4.30 present the detailed profiles according to the Route Section as defined in Table 4 and Figure 3.1.2.

The 1992 Geotechnical Interpretative Reports for the historic Crossrail scheme (Ref. [1] and [2]) provided design piezometric profiles for subsections of the route alignment between Royal Oak and Allen Gardens. However, monitoring of some of the piezometers was continued until 1998, post dating the interpretative reports by up to 6 years. In light of these data and the additional piezometric readings post-2000, the 1992 piezometric profiles have been reviewed and updated profiles are suggested in Figures 4.4.1 to 4.4.10. Figures 4.4.1 to 4.4.10 are grouped according to the revised alignment route sections (Ref. [1] and [2]) summarised in Table 4. The monitoring data of the post-2002 piezometers installed during Package 13, 16, 16A, 17B, 29⁴, 29VO1 and third party data have also been considered in reviewing these piezometric profiles. It must be emphasised that the piezometric profiles presented in these figures are only tentative suggestions as some piezometers have not stabilised yet. Therefore, additional monitoring is required to improve the definition of these profiles (see Section 5). In reviewing the 1992

⁴ Up to date Package 29 draft data, where available, has also been considered in the review.

piezometric profiles, consideration has also been given to the current groundwater levels in the deep aquifer (see Section 4.6).

The profiles presented in Figures 4.4.1 to 4.4.10 indicate the piezometric pressures to be hydrostatic from the water level in the shallow aquifer in the upper part of the London Clay Formation. Below this, piezometric pressures become sub-hydrostatic and in many cases reduce to zero in the Upnor Formation within the Lambeth Group. Hydrostatic increase in pressure with depth can again be expected below the water level in the lower aquifer. These piezometric profiles are characteristic of the underdrained conditions typical throughout the London area (Section 4.1). Towards the western end of the alignment, near Paddington Station, the piezometric profiles are observed to be hydrostatic over the depths of interest but, because of the large thickness of London Clay, no reliable instruments are yet available to define the full piezometric profile in particular for route sections P and Q, Figures 4.4.1 and 4.4.2, respectively. Package 16A ground investigation has provided more information for route sections R and S (Figure 4.4.3 and 4.4.4, respectively), however, the reliability of most of the new data is yet to be confirmed and hence the piezometric profiles have not been further defined. However, many of the Package 16A monitoring data are still stabilising or need to be verified. The soil stratigraphies shown in Figures 4.4.1 to 4.4.10 are based on interpretation of the available geological information as reported in GSIR 1&2 (Ref. [1] and [2]), Packages 13, 17A, 17B, 29, 29V01, 16, 16A and Bond Street Western Ticket Hall ground investigation data.

For route section W (Farringdon Station Figures 4.4.8 and 4.4.9) only recent monitoring data has been used to populate the presented profiles. This can be done because there is a lot of recent monitoring data in this area, including information from new installations associated with Package 13, 29 and 29VO1 ground investigations. Also, for this route section, the soil stratigraphy presented has been updated to include information obtained from Package 13, 29, 29VO1 and the BGS review of the faulting in the vicinity (Ref. [36] & [49]).

Piezometric profiles for the route sections east of Liverpool Street Station defined from post-2002 boreholes are shown in Figures 4.4.11 to 4.4.30⁵. Part of this area is currently affected by the IoD de-watering scheme. For the route sections affected by de-watering two profiles have been presented, where possible: one showing the baseline data or “natural” groundwater level (August 2008) and the other showing the current effects of Crossrail de-watering.

As with the profiles determined from the 1992 piezometers, the characteristic underdrained profile is evident in Route Sections A to J (Figures 4.4.11 to 4.4.22 respectively and Figure 3.1.2). However, the de-watering activity at IoD has led to further lowering of the piezometric pressure in the lower aquifer resulting in enhancement of the underdrained piezometric profiles (e.g. Figures 4.4.19 and 4.4.25). In particular, as a consequence of the de-watering activity,

⁵ Figure 4.4.30 present piezometric profile for the area east of Plumstead Portal – Abbey Wood.

underdrained profiles develop currently up to the Connaught tunnel. East of the Connaught tunnel, outside the subcrops of the London Clay and Lambeth Group, no effects of the IoD dewatering works have been recorded (see Figure 3.1.2). Here, the upper and lower aquifers are directly linked resulting in a conventional hydrostatic pore pressure profile (Figures 4.4.26 to 4.4.30).

Across the Isle of Dogs Station (Route Section I - Figure 4.4.21), two different piezometric profiles were recommended prior to de-watering (i.e. baseline conditions⁶). Also shown is the drawn-down water level in the lower aquifer. The piezometric profiles shown thus bound the current profile. Further information on the effects of the de-watering activities is given in Ref. [31].

Of particular interest is the hydrostatic portion of the profile evident in the Lambeth Group for Route Sections A, D, E and F to EB Chainage 12100m (Figures 4.4.11, 4.4.13, 4.4.14 and 4.4.15 respectively). It is possible to model this piezometric behaviour using Darcy's Law and the selection of appropriate strata permeabilities (Ref. [6] and [30]). This analysis suggests that to produce hydrostatic conditions, a significantly higher permeability must exist in this layer, relative to the over- and underlying strata. The profiles for Route Sections A, D, E and F (up to EB Ch 12100m) are hydrostatic within the Lambeth Group above the Mid-Lambeth Hiatus (MLH) where a large number of Sand Channels have been encountered within the Upper Mottled Beds (UMB) and the Laminated Beds (LTB). The data are consistent over a wide area and, in order for the Sand Channels to influence the pore pressure profiles to this extent, there must be a high degree of lateral interconnectivity between them. This pattern was independently confirmed along the GSIR 3 area by a detailed study of the distribution of sand channels and granular Harwich units (see GSIR 3 for more information, (ref [6]). The pore pressure profile for Route Section C does not seem to exhibit this hydrostatic profile in the Lambeth Group; this implies a lower concentration of channels in the Whitechapel area which is consistent with the borehole records (Dwg No. 1D0101-G0G00-G00-P-03023). It should be noted, however, that paucity of piezometers in the Lambeth Group, or scatter in the available data could mask the identification of other areas of hydraulic connectivity in the intermediate aquifer by identification of a hydrostatic pore pressure profile. Further discussion on the lateral continuity of Sand Channels can be found in GSIR3 (Ref. [6]). Recently completed pumping tests may also give further information in this regard (Pk13 VO2 & PK29).

⁶ The piezometric profiles are based on August 2008 data and reflect only the effects of the dewatering undertaken in Isle of Dogs for the River South project.

In contrast with the above referenced hydrostatic profile within the Lambeth Group, the central part of Route Section F (from EB Chainage 12100 to 13800m, Figures 4.4.16 and 4.4.17) depicts high level, non-hydrostatic water pressures in the Lambeth Group. The installations exhibiting this unusual high groundwater level were tested during the first phase of the piezometer remediation works – in an attempt to verify these installations and associated readings. The installations were inspected and flushed to remove any accumulated silt/blockage. Thereafter, rising head tests (RHT) were carried out and divers were installed to closely record the recovery phase (refer to Ref. [40] for further details on the remediation works carried out). Some of the investigated piezometers are still under observation (as noted on the figures), since the groundwater levels are still stabilising or it is not yet possible to draw clear conclusions on their status. Further monitoring and additional investigations will be undertaken.

Figure 3.1.2 shows the best-judgement profile lines shown on a backdrop of the geological cartoon. It illustrates clearly how the piezometric profile changes along the alignment as the ground conditions change, and the effect of Crossrail dewatering.

4.5 Shallow Aquifer

4.5.1 General

The shallow aquifer is recharged by surface water infiltration (i.e. rainfall), and from surface and subsurface sources of water such as rivers, canals, water mains and sewers (Ref. [17]). As a consequence tidal, seasonal and other less predictable fluctuations in the groundwater level of the upper aquifer are to be expected.

Approximately 27 piezometers were installed in the River Terrace Deposits (RTD) between Royal Oak Portal and Liverpool Street Station, during the 1992 ground investigations. Near-surface seepages were observed during drilling of some boreholes, however it is noted that water added to assist boring through the superficial deposits would have obscured seepages in a significant number of boreholes. Groundwater levels in the RTD were generally reported to be 0.5m to 1.0m above the top of the London Clay, Figure 3.1.2. Occasionally, higher groundwater levels (2 to 4.5m above the London Clay) were reported mostly associated with local depressions in surface of the London Clay and / or the flow regime in the upper aquifer – e.g. at the boundary between RTD terraces such as that at Pudding Mill Lane and at EB Ch12750 on the south east branch (also see ref. [1] and [2]). Figure 4.5.1 presents this historic information as contours of recorded piezometric level measurements in the RTD, taken between 1992 and 1997. The locations of the measurements points used for the contours are also indicated on the figure as the density of the data points governs the accuracy of the contours at any particular location.

A more recent contour of ground water levels in the shallow aquifer is presented in Figure 4.5.2 for the whole alignment, based on readings taken between July 2009 and August 2011. It draws from the following sources:

- Existing Crossrail shallow aquifer piezometers from the pre-2000 investigations were used where they remained functional and accessible;
- An additional 35 piezometers were installed in River Terrace Deposits (RTD)⁷ in route sections from P to X (Royal Oak Portal to Liverpool Street Station) during Packages 13,16, 16A, 29 and 29VO1 ground investigations.
- Third party data, where relevant and available, were used.

As noted above the accuracy of these contours is governed by the availability of data points, therefore, the contours should only be considered indicative of the general flow regime. Comparing Figure 4.5.1 and 4.5.2 over the area covered by GSIR 1&2, it can be seen that the more recent monitoring data (August 2011) generally confirm the 1992-1997 data, reporting groundwater level to be on average 1m above the top of London Clay, with the exception of the Farringdon Station area. In Farringdon, the recent data gives upper aquifer groundwater levels of 103 to 113m ATD, whereas no information was available in 1992 to 1997 and the contour for this period interpolated over this area. Thus the difference in Farringdon is due to: (i) absence of piezometers in this area in the 1992-1997 data (see Figure 4.5.1), (ii) availability of only a limited number of piezometers from the more recent ground investigations (see Figure 4.5.2), and (iii) the potential for significant local modifications to the upper aquifer ground water levels from obstructions, foundations, tunnels, services, etc. in this area.

To the east of Liverpool Street Station, water strikes were similarly encountered in some boreholes and 202⁸ piezometers have been installed in the shallow aquifer during the post-2002 ground investigations (including Package 29VO1). In general, the groundwater levels recorded in the upper aquifer for the section of alignment between Liverpool Street Station and EB Chainage 12400 were typically 2.4 to 3m above the top of the London Clay, Figure 3.1.2. Pudding Mill Lane Portal is in the River Lea flood plain and the Isle of Dogs branch is within the Thames flood plain from EB Chainage 12400 eastwards. The aquifer potentially becomes confined by the presence of recent alluvium (Figure 3.1.1) and the water table is generally 5 to 8m above the London Clay/Lambeth Group (Figure 3.1.2). East of Connaught tunnels, River Terrace Deposits directly overlie Thanet Sand and Chalk. Groundwater inflow from the River

⁷ 31 piezometers have also been installed in Alluvium and Made Ground.

⁸ Including installations in Alluvium and Made Ground.

Thames and River Lea control the groundwater level, which is typically between 100m and 101.5m ATD \pm the tidal fluctuations (see Figure 4.5.2). The Royal Docks at Connaught Tunnel and the Isle of Dogs have a water level that is at about 104m ATD and so appear to be largely hydraulically separated from the water level in the upper aquifer.

Groundwater flow in the shallow aquifer will regionally be to the south and east towards the River Thames and the River Lea following the surface topography. Local influences on the groundwater regime will include basements, retaining walls, buried services, tunnels, water wells, leaking boreholes and present and historic watercourses (such as the Grand Union Canal, the River Lea and the lost rivers, see Figure 4.5.2 for their locations). Furthermore, local influences such as derived tidal variations in the vicinity of the River Thames and the River Lea can be expected (see Section 4.7). Despite these limitations, it can be seen from Figure 4.5.2 a relatively low easterly hydraulic gradients along most of the alignment, except for the Farringdon area where a steeper flow gradient is apparent. The local flow at Farringdon appears to be towards the Fleet (also see Figure 3.1.2). However, it should be noted that the steep gradients could be influenced by the limited monitoring data available in this area and other reasons previously discussed. Therefore, the contours in this area may be to some extent unrepresentative. Further monitoring and investigation is required to better define the water conditions in the upper aquifer in this zone. At Limmo, a small cone of depression is located over the scour hollow at the mouth of the River Lea. This needs further confirmatory investigation, but if proven would be evidence of hydraulic connectivity and flow between the upper and lower aquifers at this location. (Also, see Section 4.7.2 for more discussion.)

In general, the flow rate in the upper aquifer is generally expected to be relatively low, as a result of the generally flat topography resulting in limited pressure head differentials. Importantly, however, the flow will dominate the migration of water-borne contaminants in the shallow aquifer. Local flows will also have an important bearing on the feasibility of ground freezing as a ground treatment option.

The 3000-series drawings (Dwg Nos. 1D0101-G0G00-G00-P-03000 to -03170) show where water strikes were encountered and the recorded groundwater water levels along with piezometer locations and the associated piezometric pressures.

Detailed evaluation of the groundwater conditions in the upper aquifer, relevant to the structures required for Crossrail Alignment, are given in the relevant Geotechnical Sectional Interpretative Report (Ref. [2], [6] and [7]).

4.5.2 Seasonal Variations

Inspection of the monitoring data from standpipes in the River Terrace Deposits suggests that there is relatively little seasonal variation in the shallow aquifer level. The data from instruments showing the greatest variation are reproduced in Figure 4.5.3, and 4.5.4.a&b. These figures cover Route Sections E, F and G (Stepney Green to Pudding Mill Lane) indicating a maximum fluctuation in the groundwater level of about 1.0m, achieved during the 2003 & 2010 winter.

Figures 4.5.3, and 4.5.4.a&b presents also the monthly rainfall data obtained from the Meteorological Office (Ref. [13]) for the same time period. The monitoring groundwater levels collected appear to exhibit a direct response to rainfall events. Further investigations have been undertaken to establish whether there is a direct linkage between rainfall and ground water

levels, comparing piezometric data recorded using Divers installed in different piezometers and daily rainfall data. Daily rainfall data were recorded almost continuously using a MET-CHECK MET126RL rain gauge for the period 14/11/2005 to 17/03/2007; rainfall data outside of this period was obtained from the Meteorological Office (Ref. [13]). Figures 4.5.5 to 4.5.13 present plots of the daily average piezometric level together with the corresponding daily rainfall.

Data collected east of the Connaught Tunnel (i.e. NW12, NW16R and NW18R, Figures 4.5.9 to 4.5.11, respectively) are dominated by large variations in the piezometric level due to tidal effects (see Section 4.7), obscuring any short or long-term responses to rainfall. For boreholes PML7, PML8, IOD15, CH6R, WP21 and WP23 no direct response to rainfall events (except for the possible flooding of the headworks of CH6R) and no significant seasonal variation are evident in the piezometric data with variations in head generally being less than 0.5m. It therefore appears that there is a direct response of the shallow aquifer to the overall events (i.e. average monthly rainfall) but not to the single/ specific event (i.e. average daily rainfall). This could depend on the magnitude of the rainfall event and also on the storativity of the aquifer and the infiltration rates. However, further monitoring will be undertaken in particular in the area where seasonal variation has been identified to aid interpretation.

4.6 Deep Aquifer

As noted in Section 4.1, the deep aquifer comprises the granular material of Thanet Sand Formation and Chalk Group in hydraulic continuity with the Upnor Formation of the Lambeth Group.

August 2011 monitoring data from Crossrail piezometers, installed in the deep aquifer, have been combined with data provided by the Environment Agency (Ref. [4]) for Jan 2011⁹ and with data provided by Thames Water for December 2010 to produce the contour plot shown in Figure 4.6.1. Note that the accuracy of these contours is governed by the available data points (as indicated on the figure), and that due to the limited quantity and temporal variations in the data, the contours should only be considered indicative of the general flow regime. In addition, construction de-watering is currently active for the construction of the Crossrail loD Station (see Section 4.2.1) and tidal variation in piezometric levels occurs in the vicinity of the River Thames and the River Lea (see Section 4.7). Use of open loop Ground Heat Source Pumps is also beginning to become a significant contributor to temporal variations of the deep aquifer ground water levels in central London. Demand for this use is seasonal.

⁹ At the time of writing, there were no data available from the Environmental Agency for August 2011.

Minimum contours level comprising 55 to 60m ATD are located in two different areas along the Crossrail alignment: in the Isle of Dog (IoD) area and in the Central London area between Paddington and Bond Street respectively. In the IoD area the minimum contour (55m ATD) is recorded at West India Dock. This cone is induced by the pumping activity which is undergoing in this area for the construction of the Crossrail IoD station (see Section 4.2.1). The contours are closely spaced to the east and the south of the Dock, indicating a steep gradient up to a distance of 500m from the pumping area, where the gradient become shallower. This is likely to be due to influence of the scour hollows and/or faulting in the Limmo peninsula area. The drawdown does extend a greater distance to the east, up to Connaught tunnel, than to the west, Stepney Green Area. This is consistent with the concept of zonal boundaries developed by Mott MacDonald in their London Basin Groundwater Model (Ref. [15]). Detailed information on the effect of the IoD de-watering activity and comparison with the predicted drawdown can be found in the specific construction de-watering report, Ref. [31].

Paddington and Bond Street, there is no great availability of data points, and the 60m ATD contour line is controlled by four EA monitoring wells, TQ28/97, TQ28/119, TQ28/153 and TQ38/263A. The gradient is relatively gradual towards Royal Oak Portal in the west (61m ATD) and towards Stepney Green Junction in the east (74m ATD). The contours are mostly equally spaced running across the figure mainly from south-west to north-east, with except for the area affected by the de-watering activity. Where there is a greater concentration of data, the gradient is the greater suggesting that the width of the band is less than indicated by the contouring routine. Thus the loss of piezometric head is concentrated into relatively narrow zones: this is consistent with the concept of zonal boundaries developed by Mott MacDonald in their London Basin Groundwater Model (Ref. [1]). The maximum level along the alignment of about 100m ATD occurs where London Clay and Lambeth Group are absent and the upper and lower aquifers are directly linked. Specific interpretation is given in the relevant GSIRs, for the areas shown on the figure.

The piezometric elevation in the deep aquifer along the Crossrail alignment is shown on the geological long section in Figure 3.1.2. This figure presents deep aquifer piezometric elevation for August 2008, before IoD de-watering activity commenced, and for August 2011 after IoD de-watering drawdown stabilised (Ref. [31], refers). The August 2011 line shows the extend of the IoD de-watering drawdown along the Crossrail alignment – Stepney Green to Connaught Tunnel along the IoD to Plumstead branch and Stepney Green to Eleanor Street Shaft along the Pudding Mill Lane branch. West of Liverpool Street the ongoing Package 16A and 29A ground investigations have provided information to better define the deep aquifer elevation for August 2011.

A substantial degree of underdrainage exists between Royal Oak Portal and Pudding Mill Lane Portal, and Stepney Green to Isle of Dogs Station. In the later, underdrainage has been

increased by the de-watering activity ongoing at the loD. Along the Crossrail alignment, the piezometric level is below the top of the aquifer¹⁰ from about EB Chainage 2500 to just past Farringdon Station. In the south east branch of the alignment, it is below the top of the aquifer from about EB Chainage 12800m to just east of loD Station. East of loD station the degree of underdrainage is minor.

The 2011 data provided by the Environment Agency has been combined with deep aquifer groundwater level trends determined from the Crossrail piezometers to produce the annual rate of change contours shown in Figure 4.6.2. Along the Crossrail alignment, the rate of change for 2007¹¹ (prior to any de-watering activity) was generally less than 1m/year. In 2008, instead, the rate of change had a maximum (reduction) of -28m/year at West India Dock, due to the loD de-watering which commenced that year. In 2009, the annual rate of change decreased and had a maximum annual rate of change value (reduction) of -3m/year at West India Dock, confirming that the target drawdown had been achieved in December 2008 and that the pumping rate had been reduced to maintenance levels during 2009/ beginning of 2010 (refer to Ref. [31] for more details). Consistent with this, the contours for 2011¹² (Figure 4.6.2) indicate a maximum (reduction) of -1m/year.

In 2009 the rate of change, along the remaining part of the alignment not affected by the loD pumping, was generally around 0.5m/year. However, in 2010 the maximum (reduction) of -3m/year was registered around Paddington. This is indicated by the EA monitoring well TQ28/53, which shows a water level change of -3.4m over the period considered. The water level change in this area is not related to the Crossrail works and is thought to be due to substantially increased abstractions by the water companies in this area in 2009 (see refs [4] & [5]). This is also confirmed by the 2011 data (Figure 4.6.2), which show an increase of 3m in the same area, indicating that any abstractions ongoing in 2010 have ceased.

The accuracy of the contours in Figure 4.6.2 is governed by the available data points (as indicated on the figure), and apart from at the data points, the contours should only be considered indicative of the present rate of change in the deep aquifer levels. Arrangements are currently being made to obtain data from additional licensed abstraction and from monitoring

¹⁰ taken as Thanet Sand since the Upnor Formation is not separately identified on Figure 3.1.2

¹¹ Note that the rate of change is determined over a one year period, generally calculated from January of each year.

¹² Note that the rate of change for 2011 has been determined using data between the period of August 2011 and September 2010.

wells owned by third parties, in order to improve the accuracy of these contours (Ref. [33] refers).

4.7 Tidal Variations

4.7.1 General

Tidal variations can occur in either the shallow or deep aquifer or both, provided that a number of criteria are met:

1. The aquifer is directly and effectively connected to a tidal waterway;
2. The average groundwater level is within the tidal range;
3. The distance from the waterway in combination with the permeability and storativity of the aquifer is sufficiently small. Note that when the aquifer is confined the storativity is effectively zero and the response is much greater.

With respect to the Crossrail alignment:

1. Both aquifers are connected to the River Thames where the London Clay and Lambeth Group are absent – this is the subcrop of the Lambeth Group as marked by the red boundary on Figure 4.7.1 and any scour hollows which penetrate to the Thanet Sand or lower. The location of the known scour hollow which penetrates to the Chalk is also shown on Figure 4.7.1. Figure 3.1.2 also shows where the two aquifers are potentially connected.
2. The shallow aquifer could be considered likely to be in direct connection throughout the relevant length of the River Thames; however the river wall can effectively cut the connection if it penetrates to the London Clay or Lambeth Group.
3. The maximum predicted tidal water level is about 104mATD at Silvertown and, consequently, if the base of the RTD is above about 105m ATD no tidal influence would be expected. The areas where the base of the drift deposits are above 105m ATD is shown shaded in white on Figure 4.7.1.
4. The aquifers are only likely to be confined where Alluvium overlies the RTD: this can be approximated by the 98m ATD contour for the base of drift deposits. This is the area shaded in yellow on Figure 4.7.1.

5. The River Lee (Bow Creek) is tidal as far north as the Bow Locks at the north-east end of the Limehouse Cut, but the Three Mills / Waterworks River which runs about 600m east of Pudding Mill Lane Portal, is fully tidal.

In combination, these factors mean that tidal effects are only likely to be significant east of Stepney Green along the Isle of Dogs branch and locally at Pudding Mill Lane portal.

In order to accurately investigate any tidal variation, it is required a high frequency of monitoring. Therefore, data loggers known as Divers were installed in standpipe and standpipe piezometers to monitor the groundwater level with a frequency faster than 1 reading per hour. To date 185¹³ installations east of Liverpool Street have been investigated and a tidal response, exhibited by the characteristic sinusoidal variation in piezometric level, has been identified in only 98 of the 185 piezometers investigated, as listed in Table 5.

Where a tidal response was identified, the data were plotted / analysed against the recorded water level in the River Thames, as shown in Figure 4.7.5. The River Thames tidal variations were plotted from the Port of London Authority tidal monitoring station at Silvertown (location shown in Figure 4.7.1). At each location, magnitude of the measured tidal response and time lag between peak river water level and peak piezometric level were evaluated and tabulated in Table 5. The data are also presented on Figures 4.7.1 to 4.7.4. The latter three Figures are a zoom in of the Woolwich, Limmo and IoD areas. In these figures the aquifers are differentiated by symbol and the magnitude of the tidal response recorded indicated by colour coding.

4.7.2 Commentary on Data

In this section it is intend to present only a summary of the main features identified during the investigation of the tidal response. Detailed tidal monitoring data, interpretation and discussion are given in the relevant tidal report Ref. [32].

As expected, east of Connaught Tunnel, where the River Thames is in direct connection to the deep aquifer and the Lambeth Group is absent (except locally at the Connaught Tunnel and at the east end of the proposed Woolwich Station) all instrument within about 1km of the river exhibit tidal response. In particular, the instruments closest to the River Thames at North Woolwich (NW16R and NW18R) and at Woolwich (WP1R and WP17P) exhibit the shortest phase shift and the largest tidal response in both shallow and deep aquifer. In agreement with this, the value of the piezometric response decreases gradually with the increase of the distance from the river, as depicted in Figure 4.7.1.

¹³ Including 1 third party monitoring well – Hanson Quarry pumping well.

Several instruments located between IoD and the Connaught Tunnel have shown a tidal response (Figures 4.7.1 to 4.7.4). In this area even where the shallow and deep aquifers are separated by the London Clay and Lambeth Group, the static pressure in the two aquifers has been in hydrostatic equilibrium before Crossrail dewatering at Canary Wharf (Figure 3.1.2 and Section 4.4). Hydrostatic equilibrium in Route Section J where the two aquifers are separated by clay layers is likely due to the complex geology features present in this area: scour hollows, which penetrate through the LG and LC, and faulting system at the Limmo Peninsula. The first provide a potential connection between the River Thames, the upper aquifer and the deep aquifer, the latter may also provide a pathway from the nearby River Thames and River Lea.

Further evidence of the hydrogeology of the Limmo and Isle of Dogs areas are provided by the tidal monitoring data obtained for Crossrail (Figures 4.7.2 and 4.7.4). Additional piezometers and more extensive monitoring have now provided a much clearer picture of the hydraulic interconnectivity around the scour hollows. Figure 4.7.3 shows the scour hollows at Limmo. Well constrained contours show the base of the drift deposits extending well below 80m ATD at this scour hollow. Significant tidal responses have been observed in piezometers in; (i) the upper aquifer, (ii) strata between the upper and lower aquifers, and (iii) the lower aquifer. The tidal piezometers cluster around scour hollow between EB chainage 15600 and 15800 approximately. Large tidal variations (>1m) are observed in instruments up to 140m away from the 80m ATD contour for the base of drift. A tidal response is even observed in piezometers in the London Clay (e.g. CH15P (LC(A2)), CH16R (LC(B) & LC(A2)), CH79 (LC(A2)), CH80 (LC(A2)) and CH82 (LC(A2)), refer to Table 5 for more details). Calculations showed that the observed London Clay pore pressure cycles were one or two orders of magnitude greater than that attributable to undrained cyclic loading by the tidal River Lea and River Thames (ref [37]). The observed tidal response must therefore be due to direct hydraulic connection to either or both rivers, likely through silt layers and the scour hollow/ faulting.

Figure 4.7.4 shows a similar plot for the scour hollow near the Isle of Dogs, between EB Ch 14300 to 14900 approx. Contours show that the base of the drift deposits extends below 70m ATD. Looking at the adjacent ground conditions, as indicated in Figure 3.1.2, the scour hollow should therefore penetrate at least down to the Thanet Sand. Again, a significant tidal response is registered by piezometers in the upper aquifer, lower aquifer and strata in between. The tidal piezometers are observed up to 400m from the 80m ATD base of drift contour. These observations all indicate the existence of hydraulic connectivity in this area between the upper aquifer, intermediate strata, the lower aquifer and the River Thames.

With regard to the area between IoD and Stepney Green, and from Stepney Green and Pudding Mill Lane, only one instrument IOD19P showed tidal response, Figure 4.7.1. Here London Clay and Lambeth Group are present through the area, separating the shallow and deep aquifers. The unexpected (but isolated) result obtained for the IOD19P Thanet Sand piezometer suggested the possibility of a local connection between the River Thames and the deep aquifer. Partly for this reason, this piezometer was investigated under the remediation works package. During this works a leakage was identified in this piezometer (Ref. [40]). The leakage was due to faulty connection(s) in the piezometer pipe between 30 and 32m depth. The Lambeth Group (LMB) was identified in the borehole log to exist at this depth. Consequently, it is believed that the piezometer is reading the (higher) groundwater level within the Lambeth Group instead of that in the Thanet Sand Formation. Consequently, it is planned to undertake further monitoring to aid investigation of the significant tidal variation in the Lambeth Group implied by this new information.

5 PLANNED GROUNDWATER MONITORING AND INTERPRETATION

The following further groundwater monitoring and interpretation of the recorded data are planned:

1. Complete remedial works on problematic piezometers.
2. Three monthly monitoring of all functional piezometers (1992 & post-2002). Further details on the monitoring strategy are given in Strategy Monitoring report in Ref. [33]
3. Update this report regularly as monitoring information become available.
4. Review the groundwater levels recorded for the shallow and deep aquifers and the associated flow regimes using latest available data.

6 REFERENCES

- [1] Arup Geotechnics (1992). CrossRail: *Geotechnical Interpretative Report – Section Interpretative Report 1& 2 – Torquay Street to Charing Cross Road. And Charing Cross Road to Vallance Road.*
- [2] Geotechnical Consulting Group (2008). Cross London Rail Links Ltd, Crossrail Line 1, *Geotechnical Sectional Interpretative Report 1&2 Volumes 1 to 3*, Royal Oak Portal to Liverpool Street Station, Revision A, Report No. 1D0101-C1G00-00549 to -00551.
- [3] Eijkelkamp Agrisearch Equipment (2003). Diver Operating Instructions
- [4] Environment Agency (2011). Groundwater data for Chalk-Basal Sands Aquifer of the Central London Basin up to January 2011
- [5] Environment Agency (2011). *Management of the London Basin Chalk Aquifer*, 2011.
- [6] Geotechnical Consulting Group (2010). Crossrail Limited, *Geotechnical Sectional Interpretative Report 3 Volumes 1 to 3*, Central Area Liverpool Street to Pudding Mill Lane and Isle of Dogs, Revision E, Report No. 1D0101-C1G00-00507 to -00509.
- [7] Geotechnical Consulting Group (2010). Crossrail Limited, *Geotechnical Sectional Interpretative Report 4 Volumes 1 to 3*, Isle of Dogs to Plumstead, Revision C, Report No. 1D0101-C1G00-00520 to -00522.
- [8] Geotechnical Consulting Group (2008). Cross London Rail Links Ltd, Crossrail Line 1, *Multi-level piezometer trial at Stepney Green: Evaluation and interpretation of 3 systems*, Revision A, Report No.1D0101-G0G00-00548.
- [9] Geotechnical Consulting Group (2008). Cross London Rail Links Ltd, Crossrail Line 1, *MPS Pumping Test at Whitechapel*. In preparation

- [10] Hight, D.W., Ellison, R.A., Page, D.P. (2001). *Engineering in the Lambeth Group*. CIRIA Funders Report/CP/83.
- [11] King, C. (1981). *The Stratigraphy of the London Clay and Associated Deposits. Tertiary Research Special Paper No. 6*, Backhuys (publ). 158pp.
- [12] Land and Boundary Information System (LABINS). *Tidal Predictions*. data.labins.org/2003/SurveyData/WaterBoundary/MHW/documents/9tidepredictions.pdf
- [13] Meteorological Office Hadley Observation Centre (2005-2011). Daily and Monthly Rainfall for the SE of England.
- [14] Ove Arup & Partners Limited (August 2010) Crossrail Alignment, Revision S Track Horizontal Alignment CAD FILE, Revision P09, C122-OVE-R4-DMA-CR001-11000.
- [15] Mott MacDonald (2005). Crossrail Line 1, Assessment of Water Resource Impacts, Technical Report, Report No. 1E0321-1E00-00005, Final Issue, February 2005.
- [16] Norwest Holst Soil Engineering Ltd (2004). *Monitoring Report for Cross London Rail Links Ltd 1992*, Contract No. F13316.
- [17] Construction Industry Research Association (1993). *A study of the impact of urbanisation on the Thames Gravel aquifer*, CIRIA Report 129.
- [18] Page, D. & Skipper, J. (2000). Lithological characteristics of the Lambeth Group. *Ground Engineering* 33 (2), pp 38-43.
- [19] Port of London. *Tide Tables and Port Information (2004 to 2011)*. North Woolwich Tide Tables.
- [20] Simpson, B., Blower, T., Craig, N.R. & Wilkinson, W.B. (1989). *The engineering implications of rising groundwater levels in the deep aquifer beneath London*. CIRIA Special Publication 69.

- [21] Geotechnical Consulting Group (2007). Cross London Rail Links Ltd, Crossrail Line 1, *Geotechnical Desk Study Addendum*, Isle of Dogs to Plumstead Portal: Isle of Dogs Station, Revision B, Report No. 1D0101-C1G16-00526.
- [22] Withers, A.D. (1996). Dewatering and De-pressurisation system for the Thanet Sands and Chalk Aquifer – Case Studies from the Jubilee Line Extension Project.
- [23] Nicholson, D, Sleight, A., Mayo, K. (2006). Canary Wharf Development – Dewatering of Thanet Sands for pile construction – A Case Study. (Draft Paper)
- [24] Arup Geotechnics Ltd. (2001). Canary Wharf – Decommissioning of the Upper and Lower Aquifer Dewatering Systems.
- [25] Mott MacDonald (2004). Cross London Rail Links Ltd, Crossrail Line 1, *Isle of Dogs Station – Hybrid Bill Design Report*. Volume 1 and 2. Report No. 1D0200-C1S16-10250.
- [26] Ove Arup & Partners (1998). Canary Wharf Dewatering Settlements. Prediction of settlements due to the dewatering of lower aquifer. November 1998. Job No. 56117/60
- [27] Geotechnical Consulting Group (2007). Cross London Rail Links Ltd, Crossrail Line 1. *Geotechnical Desk Study Addendum*, Isle of Dogs to Plumstead Portal: Limmo Peninsula, Revision A, Report No. 1D0101-C1G16-00516.
- [28] Mayo K, (2008). Groundwater regime and pumping at Canary Wharf email received on 09 September 2008.
- [29] British Waterways (2008). Dock water levels email received on 05 March 2008.
- [30] Geotechnical Consulting Group (2008). Cross London Rail Links Ltd, Crossrail Line 1. Relative Permeability and Pore Water Pressure Profiles, Revision A, Report No. 1D0101-C1G00-00565.

- [31] Geotechnical Consulting Group (2011). Crossrail Limited. Monitoring of Construction De-Watering – September 2011, Report No. CRL1-GCG-C2-RAN-CRG03-00001, Rev. 6.

- [32] Geotechnical Consulting Group (2011). Crossrail Limited. Monitoring of Groundwater Response to Tidal Variations, Report No. CRL1-GCG-C2-RAN-CRG03-00003 Rev. 1.

- [33] Geotechnical Consulting Group (2009). Crossrail Limited. Ground Water Monitoring Strategy, Revision A, Report No. 1D0101-G0G00-00571.

- [34] Geotechnical Consulting Group (2008). Note on proposed remedial works for Crossrail piezometers, November 2008. Sent to Ursula Lawrence on 18/11/2008.

- [35] Geotechnical Consulting Group (2010). Crossrail Limited. Interpretation of Faulting along the Crossrail Alignment, Report No. CRL1-GCG-C2-RST-CRG03-00001. In preparation.

- [36] Aldiss D. T., Entwisle D. C. and Terrington R. L. (2009). British Geological Survey. A 3D geological model for the proposed Farringdon underground railway station, Central London.

- [37] Geotechnical Consulting Group (2007). Cross London Rail Links Ltd, Crossrail Line 1. Multi-Level Piezometer Trial at Stepney Green: Solinst Continuous Multichannel Tubing CMT7, Revision A, Report No. 1D0101-G0G00-00545.

- [38] Geotechnical Consulting Group (2007). Cross London Rail Links Ltd, Crossrail Line 1. Multi-Level Piezometer Trial at Stepney Green: Vibrating Wire Sensors In Grouted Borehole, Revision A, Report No. 1D0101-G0G00-00546.

- [39] Geotechnical Consulting Group (2007). Cross London Rail Links Ltd, Crossrail Line 1. Multi-Level Piezometer Trial at Stepney Green: Solexpert Multiport Sampling System, Revision A, Report No. 1D0101-G0G00-00547.

- [40] Geotechnical Consulting Group (2010). Crossrail Limited, Interpretation of remedial works for Crossrail piezometers, Report No. CRL1-GCG-C2-RSI-CRG03-00001. In preparation.
- [41] Soil Mechanics (2010). Ground investigation for Stepney Green Pumping Tests, Crossrail contract 1179 Package13 VO2. Ref. No. D9904, Issue 1 Rev 2, March 2010.
- [42] Norwest Holst Soil Engineering Ltd (2010). Report on a pump test at Crossrail Package 25, Pudding Mill Lane. Draft copy, 26th March 2010.
- [43] Geotechnical Consulting Group (2010). List of proposed remedial works for Crossrail piezometers 2010, dated 06/07/2010).
- [44] Geotechnical Consulting Group (2006). Cross London Rail Links Ltd, Geotechnical Desk Study Farringdon Station, Revision A, Report No. 1D0101-C1G10-00531, October 2006.
- [45] Geotechnical Consulting Group (2006). Cross London Rail Links Ltd, Geotechnical Desk Study Tottenham Court Road Station, Revision A, Report No. 1D0101-C1G08-00532, November 2006.
- [46] Geotechnical Consulting Group (2009). Additional note on remediation Work, June 2009. Email from COM to Andrew Doe dated 18/06/2009.
- [47] Geotechnical Consulting Group (2008). Crossrail Limited, Variable Head Permeability Testing, Revision C, Report No. 1D0101-G0G00-00517.
- [48] Ove Arup & Partners Limited (2010). Crossrail Limited, Ground Investigation Schedules 2&3: Exploratory holes Package 27 (Sentinel Wells), Document No. C122-OVE-C2-TSC-CRG01-00002.
- [49] Geotechnical Consulting Group (2010). Crossrail Limited, Ground model extract for input into development of geotechnical baseline reports Farringdon Station, Report No. CRL1-GCG-C2-RDE-MI23-00001

- [50] Fugro Engineering Services Limited (2010). Crossrail Limited, Package 16A, Royal Oak to Farringdon, Bond Street Station – Factual Report on Ground Investigation.

- [51] GCG (2010) “Report on the ingress of water and sand into the Jubilee Line tunnels in the Bond Street area” Rev 1 dated 16/11/2010; report by Dr J. Skipper for Tubelines (confidential).

- [52] Berry, F. G. (1979). Late Quaternary scour-hollows and related features in central London. *Quart. Jnl. Engng Geol.* Vol. 12, pp. 9-29.

- [53] Lenham J., Meyer V., Edmonds H., Harris D., Mortimore R., Reynolds J. and Black M. (2006). What lies beneath: surveying the Thames at Woolwich. *Proceedings of the Institution of Civil Engineers: Civil Engineering*, Vol. 159, Issue 1, pp 32-41

- [54] Lawrence U. (2011). Dewatering Programme email to Marianna Caianiello dated 29/09/2011 (11.30am)

- [55] Geotechnical Consulting Group (2010). Crossrail Limited, Groundwater Level Monitoring. Report No. CRL1-GCG-C2-RAN-CRG03_0002 Rev.1 dated 30/11/10



TABLES

Table 1. Generalised geological succession.

Period	Series	Deposits
Quaternary	Holocene	Made Ground Alluvium
	Pleistocene	Langley Silt River Terrace Deposits
Palaeogene	Eocene	London Clay Formation Harwich Formation
	Palaeocene	Lambeth Group Thanet Sand Formation
Cretaceous	Upper Cretaceous	Chalk

Table 2. Crossrail Alignment ground investigations.

Package ^[3]	Description	Route Sections ^[1]	Borehole prefix ^[2]	Commencement date
A	Paddington to Balderton Street	-	P, RT	February 1992
B	Balderton Street to Charing Cross Road	-	B, T, RT	March 1992
C	Charing Cross Road to Aldersgate Street	-	RT, F	March 1992
D	Alderstgate Street to Vallance Road	-	RT, L	April 1992
1	Whitechapel Station	C	WH	September 2002
2	Liverpool Street to Bow and Isle of Dogs (Phase 1)	A, D, E, F, G H	LW, SG, BT, IOD	November 2002
3	Liverpool Street to Bow and Isle of Dogs (Phase 2)	A, B, E, H	LW, SG, IOD	August 2003
4	Isle of Dogs to Plumstead (Phase 1)	J to M	CH, NW	March 2004
6	Woolwich Reach Geophysical Investigation	N	Not Applicable	January 2004
7	Woolwich Reach Ground Investigation	N	TRC	March 2004
8	Liverpool Street to Bow and Isle of Dogs (Phase 3)	F, G	BT, PML, IOD	November 2004
9	Plumstead Portal	O	WP	April 2005
10	Isle of Dogs to Plumstead (Phase 2)	N, O	WP	November 2005
11	Isle of Dogs to Plumstead (Phase 3)	I to N	IOD, CH, NW	August 2006
12	Liverpool Street to Bow (Pudding Mill Lane) and Isle of Dogs (Phase 4)	A, C, D, E, F, G	LW, SG, BT, PML, WH	September 2006
13	Farringdon Station to Whitechapel Station	V to X, A, C	F, L, LW, RT, SG, WH	March 2009
13 VO1	Whitechapel Station	C	WH	July 2009
13 VO2	Stepney Green	E	SG	July 2009
13 VO3	Farringdon Station	W	F	July 2009
14	West India North Dock, Bow Creek,	G, I and J	Not applicable	June 2006

Package ^[3]	Description	Route Sections ^[1]	Borehole prefix ^[2]	Commencement date
	Lee Navigation and City Mill River Geophysical Investigations			
15	Isle of Dogs Station	H to I	IOD	April 2007
15A	Isle of Dogs Station	I	IOD	December 2007
16	Royal Oak Portal to Farringdon Station	P to V	P, T, BST, RT	January 2008
16A	Royal Oak Portal to Farringdon Station	P to V	P, T, BST, RT	March 2010
17A	Paddington Station	R	RT	January 2009
17B	Royal Oak Portal	P	ROP	March 2009
18	North Woolwich to Woolwich	N1	TRC	2007
19	Costume House Station to North Woolwich	L to M	CH, NW, WS, TP	June 2009
19A	Limmo Peninsula	J	CH, WS, TP	September 2009
20	Woolwich to Plumstead Portal	N2 to N3	WP	October 2008
21	Plumstead Portal to Abbey Wood	O	WP	January 2009
22	Victoria & Albert Dock	L	Not applicable	2009
23*	Tunnelling Academy	Not applicable	CBR, IL, TP	Not finalised
24*	North Pole Depot	Not applicable	DP, NP, TP, WS	Not finalised
25	Pudding Mill Lane	G	PML, TP, WS	June 2009
25 VO1	Pudding Mill Lane	G	PML, TP, WS	December 2009
25VO2	Pudding Mill Lane	G	PML, TP, WS	June 2010
26*	Wallasea Island	Not applicable	-	Not finalised
27*	Sentinel BH	Not applicable	SN	August 2010
28	Bow Creek Geophysics	J	Not applicable	October 2009
29	Farringdon Station to Whitechapel Station	V to X, A, C	BT, F, L, LW, RT, SG, WH, WS	March 2010
29VO2	Farringdon Station to Stepney Green	V to X, A, to D	BT, F, L, LW, RT, SG, WH,	July 2010



Package ^[3]	Description	Route Sections ^[1]	Borehole prefix ^[2]	Commencement date
			WS	
30	Cross Passages South-East of Farringdon	X, A, J, K and L	IOD, CH, TP	August 2010
31	North Woolwich and Plumstead Portals	M, O	NW	July 2010
33*	Old Oak Common	Not applicable	NP, TP, WS	February 2010
35	Connaught Tunnel	L	NW	March 2011
36	Canary Wharf Box	I	Not applicable	December 2010
37	Woolwich Station	M	WP	March 2011
BST WTH ^[4]	Bond Street	T	BST	March 2011

^[1] as defined in the GCG Geotechnical Sectional Interpretative Reports (Ref. [2], [6] and [7]).

^[2] P = Paddington Station
 T = Tottenham Court Road Station
 L = Liverpool Street Station
 WH = Whitechapel Station
 SG = Stepney Green
 IOD = Isle of Dogs
 NW = North Woolwich
 PML = Pudding Mill Lane
 TP = Trial Pit
 ROP = Royal Oak Portal
 CBR=Californian Bearing Ratio
 DP= Dynamic Probe
 SN= Sentinel
 B = Bond Street Station
 F = Farringdon Station
 RT = Running Tunnel
 LW = Liverpool Street to Whitechapel Stations
 BT = Bow Triangle
 CH = Custom House
 TRC = Thames River Crossing
 WP = Woolwich to Plumstead
 BST = Bond Street Station
 WS = Window sampling
 IL= Ilford Tunnel
 NP= North Pole Depot

^[3] * signifies not along the underground section of the Crossrail alignment

^[4] BST WTH = Bond Street Station Western Ticket Hall Ground Investigation

Table 3. Construction of De-watering activities programme

Crossrail Worksite ⁴	Main Construction Start	De-watering Development	De-watering Required	Strata	Reporting Start
Isle of Dogs Station	Q1 2009	Q3 2008	63m ATD	Thanet / Chalk	Q3 2009
Woolwich Station ¹	Q3 2011	Q1 2012	Localised ~92m ATD	Thanet / Chalk	Q1 2012
Connaught Tunnel	Q2 2011	Q1 2012	88m ATD	UF / Thanet / Chalk	Q1 2012
Plumstead Portal ²	Q1 2012	Q2 2012	Localised >90m ATD	RTD/ Thanet / Chalk	Q2 2012
Limmo Shaft	Q4 2011	Q2 2012	62m ATD (tbc)	Thanet / Chalk	Q2 2012
North Woolwich Portal ²	Q1 2013	Q2 2013	Localised >90m ATD	RTD & Chalk	Q2 2013
Eleanor Street Shaft	Q4 2013	Q3 2014	<72m ATD (tbc)	HF/LG; UF/TS	Q3 2014
CP13	Q1 2013	Q3 2012	59m ATD	Chalk	Q3 2012
CP14	Q1 2013	Q4 2012	68m ATD	Chalk	Q4 2012
CP15	Q2 2014	Q2 2014	NF	Chalk	Q2 2014

^[1] Pumping inside the station box

^[2] Pumping inside the box with recharge to the River Terrace Deposit

^[3] NF = Not Finalised

^[4] CP = Cross Passage

Table 4. List of Crossrail Alignment route sections.

Route Section	From	To	Construction elements
P	Royal Oak Portal		Tunnel eyes
			TBM reception shaft
			Cut-and-cover tunnel
			Retained cut
Q	Royal Oak Portal	Paddington Station	Running tunnel
			Sump
			Crosspassage CP1
R	Paddington Station		Station
S	Paddington Station	Bond Street	Running tunnels
			Sump
			Crosspassages CP2, CP3 and CP4
T	Bond Street	Tottenham Court Road Station	Bond Street Station
			Sump
			Crosspassage CP4a
			Running tunnels
U	Tottenham Court Road Station		Station
V	Tottenham Court Road	Farringdon Road	Running tunnels
			Fisher Street Shaft
			sumps
			Fisher Street Crossover
			Crosspassage CP5
W	Farringdon Station	Liverpool Street	Farringdon Station
			Sump
			Crosspassage 5a
			Running tunnels
X	Liverpool Street Station		Station
A	Liverpool Street Station	Whitechapel Station	Running tunnels
			Crosspassages CP6 and CP8
			Sump
C	Whitechapel Station		Station
D	Whitechapel	Stepney Green	Running tunnels
			Crosspassage CP9
			Sump

Route Section	From	To	Construction elements
E	Stepney Green		Step-plate junctions
			Shafts
F	Stepney Green	Bow Triangle	Running tunnel
			Niche
	Mile End Park		Shaft
	Eleanor Street		Shaft
	Bow Triangle	River Lea	Running tunnels
G	River Lea	Marshgate Lane	Padding Mill Lane Portal Cut-and-cover tunnel
	Marshgate Lane	Waterworks River	Viaduct
H	Stepney Green	West India Quay	Running tunnels
			Crosspassages CP10, CP11 and CP12
			Sump
I	Isle of Dogs Station		Station platforms
			Running Tunnels
J	Isle of Dogs Station	Victoria Dock Portal	Running tunnels
			Crosspassages CP13, CP14 and CP15
	Limmo Peninsula		Sump
K	Victoria Dock Portal		Shaft
			Tunnel eyes
			TBM reception shaft
			Cut-and-cover tunnel
			Retained cut
L	Victoria Dock Portal	North Woolwich Portal	At-grade track and Connaught tunnel (existing)
M	North Woolwich Portal		Retained cut
			Cut-and-cover tunnel
			TBM reception shaft
			Tunnel eyes
N1	North Woolwich	Woolwich	Running tunnels
			Crosspassages CP16 and CP17
			Sump
N2	Woolwich Station		Station



Route Section	From	To	Construction elements
N3	Woolwich	Plumstead	Running tunnels
			Crosspassages CP18 and CP19
O	Plumstead Portal		Tunnel eyes
			TBM reception shaft
			Cut-and-cover tunnel
			Retained cut

Table 5. Details of tidal monitoring.

Piezometer ^[1]	Date	Measured Tidal Amplitude (m)	Recorded Piezometric Amplitude (m) ^[2]	Time lag (hh:mm) ^[2]	Distance from River Thames (m)	Base of Drift (mATD)
Area 1: Plumstead Portal to Connaught Tunnel						
NW6R SP (TS)	10/04/09	7.0	0.045	07:00	350	91.72
NW7 S (RTD)	09/08/10	6.25	0.51	02:00	262	90.00
NW7 SP (CK)	28/07/10	6.0	0.30	03:20	262	90.00
NW10R S (RTD)	10/04/09	7.0	0.49	02:05	250	89.26
NW11R S (RTD)	10/04/09	7.0	0.42	02:50	250	90.55
NW11R SP (CK)	10/04/09	7.0	0.44	02:55	250	90.55
NW12 S (RTD)	19/09/05	6.9	0.46	02:45	205	88.72
NW12 SP (CK)	05/12/09	6.8	0.09	04:10	205	88.72
NW15R S (RTD)	10/04/09	7.0	0.72	02:25	200	90.68
NW15R SP (CK)	10/04/09	7.0	0.70	02:20	200	90.68
NW18R S (RTD/CK)	21/08/05	6.9	2.80	00:20	50	90.02
NW18R SP (CK)	09/04/09	6.9	2.90	00:35	50	90.02
NW16R S (AL/RTD)	11/03/05	7.0	3.20	00:35	30	89.47
NW16R SP (CK)	10/04/09	7.0	3.20	00:35	30	89.47
NW20P S (RTD)	10/04/09	7.0	0.52	03:00	200	89.74
NW27R S (CK)	10/04/09	7.0	0.56	03:20	200	90.57
NW29R SP (RTD)	09/08/2010	5.8	0.06	04:10	226	91.51
NW29R SP (CK)	28/07/2010	6.0	0.15	04:30	226	91.51
WP1R S (MG/TS)	16/12/08	6.7	1.44	00:10	24	97.31

Piezometer ^[1]	Date	Measured Tidal Amplitude (m)	Recorded Piezometric Amplitude (m) ^[2]	Time lag (hh:mm) ^[2]	Distance from River Thames (m)	Base of Drift (mATD)
WP1R SP (CK)	16/12/08	6.7	2.00	00:20	24	97.31
WP17P SP (TS)	16/12/08	6.7	1.12	00:30	78	99.00
WP17P SP (CK)	16/12/08	6.7	1.36	00:30	78	99.00
WP7R S (TS)	27/05/09	6.8	0.16	01:00	420	105.16
WP7R SP (CK)	16/12/08	6.7	0.56	00:25	425	105.16
WP35R SP (CK)	16/12/08	6.7	0.34	02:00	520	90.18
WP41R SP (TS)	19/09/09	7.3	0.03	02:00	525	104.91
WP41R SP (CK)	19/09/09	7.3	0.13	02:00	525	104.91
WP44 SP (TS)	19/09/09	7.3	0.025	02:30	700	99.66
WP44 SP (CK)	19/09/09	7.3	0.20	01:20	700	99.66
WP46R SP (CK)	19/09/09	7.3	0.14	03:00	928	90.52
WP47R SP (RTD)	19/09/09	7.3	0.05	04:30	1225	87.61
WP48RA SP (RTD)	19/09/09	7.3	0.04	04:30	1330	89.71
WP49R S (RTD)	19/09/09	7.3	0.035	04:45	1400	87.73
WP51RA S (RTD)	19/09/09	7.3	0.05	04:15	1190	87.57
WP51RA SP (CK)	19/09/09	7.3	0.04	05:15	1190	87.57
WP6R SP (CK)	25/06/09	6.9	0.52	00:50	420	105.66
WP37P S (TS)	25/06/09	6.8	0.04	03:20	350	106.32
WP37P SP (CK)	25/06/09	6.8	0.4	01:30	350	106.32
WP39R SP (TS)	25/06/09	6.8	0.29	01:05	525	107.26
WP39R SP (CK)	25/06/09	6.8	0.29	02:20	525	107.26

Piezometer ^[1]	Date	Measured Tidal Amplitude (m)	Recorded Piezometric Amplitude (m) ^[2]	Time lag (hh:mm) ^[2]	Distance from River Thames (m)	Base of Drift (mATD)
WP40R SP (TS)	25/06/09	6.8	0.36	01:05	490	102.7
WP40R SP (CK)	25/06/09	6.8	0.67	00:45	490	102.7
WP42R SP (CK)	25/06/09	6.8	0.17	03:00	560	98.73
WP43R SP (CK)	25/06/09	6.8	0.12	02:25	700	99.77
WP86PB SP (CK)	25/06/09	7.0	0.55	00:50	350	104.38
WP96 SP (CK)	25/06/09	6.8	0.44	01:25	455	102.67
WP96 SP (CK)	25/06/09	6.8	0.45	00:50	455	102.67
WP97R SP (TS)	25/06/09	6.8	0.19	01:20	455	102.41
WP38R SP (CK)	26/06/09	6.8	0.06	02:50	385	104.41
WP18P S (UF)	15/12/08	6.8	0.02	02:15	590	103.4
WP10R SP (UF)	16/12/08	6.7	0.20	01:00	625	105.57
WP10R SP (CK)	16/12/08	6.7	0.34	00:40	625	105.57
WP13R SP (CK)	16/12/08	6.7	0.20	01:40	710	104.64
WP19R SP (CK)	16/12/08	6.7	0.19	01:40	845	109.78
WP14R SP (CK)	15/01/09	7.0	0.20	01:00	820	105.86
WP21R SP (RTD)	15/11/05	6.1	0.075	02:30	1025	91.51
WP23R SP (RTD)	15/11/05	6.1	0.02	03:45	1130	90.53
WP25R SP (RTD)	15/01/09	7.0	0.06	02:40	1190	91.47
WP25R SP (TS)	15/01/09	7.0	0.08	04:00	1190	91.47
Area 2: Connaught Tunnel to Isle of Dogs						
CH1R SP (CK)	28/10/08	6.0	0.08	02:15	480	94.80
CH35P SP (TS)	28/10/08	6.0	0.09	01:00	480	94.80


Piezometer ^[1]	Date	Measured Tidal Amplitude (m)	Recorded Piezometric Amplitude (m) ^[2]	Time lag (hh:mm) ^[2]	Distance from River Thames (m)	Base of Drift (mATD)
CH2R SP (TS)	07/05/08	7.1	0.13	01:30	377	92.51
CH3R SP (CK)	28/10/08	6.0	0.23	01:40	300	88.40
CH4R SP (HF)	03/08/07	6.6	0.09	02:15	258	92.74
CH4R SP (TS)	12/01/09	6.4	0.48	01:40	258	92.74
CH6R SP (RTD)	07/10/06	6.9	0.54	03:25	160	94.27
CH7RA SP (TS)	12/03/08	7.5	0.55	01:00	210	94.03
CH9R SP (LC(A2))	04/03/10	7.4	0.08	03:20	304 (13)	95.84
CH9R SP (UF)	04/03/10	7.2	0.09	01:50	304 (13)	95.84
CH13 S (LTB)	26/04/09	6.8	1.33	01:35	150 (60)	93.1
CH14R S (AL/RTD)	26/04/09	6.8	3.0	00:50	(40)	93.07
CH14R SP (UF)	21/04/08	7.2	0.22	02:00	(40)	93.07
CH15P S (RTD)	26/04/09	6.8	2.25	01:00	(56)	93.53
CH15P SP (LC(A2))	21/04/08	7.2	0.23	02:00	(56)	93.53
CH16R SP (LC(B))	21/04/08	7.2	1.23	01:30	(115)	93.80
CH16R SP (LC(A2))	21/04/08	7.2	0.1	01:00	(115)	93.80
CH17RA SP (SU)	26/04/09	6.8	0.3	01:20	(85)	93.88
CH27 SP (TS)	26/04/09	6.8	0.15	03:25	1000	92.35
Hanson Quarry pumping well (CK)	10/05/09	6.3	0.99	06:55	35	No log available
CH48 SP (HF)	14/07/10	6.2	0.16	04:00	(327)	94.61
CH56RB S (HF)	30/04/10	6.64	1.0	02:20	(53)	94.10
CH57R S (CK)	30/03/10	7.0	0.9	00:30	(87)	94.50

Piezometer ^[1]	Date	Measured Tidal Amplitude (m)	Recorded Piezometric Amplitude (m) ^[2]	Time lag (hh:mm) ^[2]	Distance from River Thames (m)	Base of Drift (mATD)
CH61R S (CK)	30/03/10	7.0	0.85	00:00	(66)	94.27
CH72RC S (TS)	30/03/10	7.0	1.07	00:40	(55)	92.14
CH79 SP (LC(A2))	30/03/10	7.4	0.36	03:50	(29)	93.41
CH80 SP (LC(A2))	30/03/10	7.1	1.05	02:30	(22)	94.88
CH81 SP (RTD)	28/07/10	6.2	0.98	01:50	(5)	74.90
CH82 S (RTD)	28/07/10	6.0	0.95	02:00	(8)	92.22
CH82 SP (LC (A2))	28/07/10	6.0	0.05	04:00	(8)	92.22
CH83R S (TS)	30/03/10	7.1	1.04	00:40	(64)	93.11
CH87R SP (SU/LTB)	30/3/10	7.1	N/D	N/D	(72)	94.42
CH88R S (SU/LTB)	30/03/10	7.1	1.0	01:30	(81)	94.73
CH89R S (HF)	30/03/10	7.1	1.0	01:00	(70)	94.27
CH90R S (TS)	30/03/10	7.1	1.0	01:10	(68)	93.35
CH91R S (CK)	30/03/10	7.1	1.0	00:10	(43)	93.50
CH92RA S (HF)	18/04/10	7.0	0.5	02:20	(41)	93.47
CH93R S (SU/LTB)	30/03/10	7.1	1.1	01:00	(60)	94.00
Area 3: Isle of Dogs to Stepney Green						
IOD19P SP (TS)	15/11/08	6.7	0.30	03:50	334	103.16

^[1] S Standpipe
SP Standpipe Piezometer
O Open hole in response zone

^[2] N/D Not determined

FIGURES



DRIFT	
	Worked Ground
	Made Ground
	Worked Ground and Made Ground
	Landscaped Ground
	Disturbed Ground
	Kempton Park Gravel
	Taplow Gravel
	Hackney Gravel
	Lynch Hill Gravel
	Finsbury Gravel
	Boyn Hill Gravel
	Black Park Gravel
	Enfield Silt
	Langley Silt
	Undifferentiated
	Westmill Gravel
	Gerrards Cross Gravel
	Dollis Hill Gravel
	Woodford Gravel
	Head, undifferentiated: variable pebbly sandy clay
	Head, gravel: abundant well rounded flint pebbles in clayey matrix
	Tidal River or Creek Deposits: present day intertidal mudflat
	Peat
	Alluvium: mainly sand, silt and clay with some gravel
	Roding Silt
	Ilford Silt
	Woodford Gravel, Pre-diversionary Thames River Terrace Deposit: gravel, sandy and clayey in part
	Glaciofluvial Deposits: sand and gravel
	Glaciolacustrine Deposits: interbedded sand, silt and clay
	Till: mainly chalky sandy and pebbly clay
	Interglacial Lacustrine Deposits: Organic-rich mud and sand
	Sand and Gravel of Uncertain Origin: pebbly gravel and sand
	Clay-with-flints: unworn flints in clay matrix; patches of pebbly clay and sand
	Stanmore Gravel: well rounded flint gravel, sandy and clayey in part
	Well Hill Gravel: sand and gravel, clayey in part
	Chelsfield Gravel: well rounded flint gravel with unworn flint in sandy matrix



The relationships of the principal Quaternary deposits are shown schematically in a tablet below

----- Geological boundary, Drift
 - - - - - Geological boundary, Solid

Broken lines denote inferred boundaries

Within older urban areas, much of the surface has been partially or wholly disturbed by human activity and thus made, worked and landscaped ground are not delimited

Source:
 British Geological Survey
 1:50,000 scale, Solid and Drift Geology,
 Sheet Nos. 256 (1993), 257 (1996), 270 (1998) and 271 (1998)
 Reproduced under Licence No. C06/001-CSL British Geological Survey. ©NERC. All rights reserved.



Notes:

- Do not scale off these drawings. The information shown is only indicative and should not be relied upon. Precise information on groundwater monitoring is provided in Groundwater Level Monitoring Report Documentum No. CRL1-GCG-C2-RAN-CR03-0002 Rev.2 and precise information on tidal variation is provided in Monitoring of Groundwater Responses to Tidal Variations, Report No. CRL1-GCG-C2-RAN-CR03-0003 Rev. 1
- The groundwater pressure profiles shown represent best-judgement lines fitted to data collected up to August 2011.
- Each groundwater pressure profile presents conditions over a chainage range that is between 100 and 2000m long. Each profile therefore reflects the average ground conditions over its chainage range. This may lead to some discrepancy between the profiles and the local ground conditions at the position at which the profiles have been presented in this figure.
- Temporal variations in the deep aquifer level could also lead to differences relative to the information presented in this figure (e.g. tidal variations, variations due to changes in deep aquifer abstraction rates etc.).
- The geological information shown is simplified and approximate based on drawings 1D0101-G0G00-G00-P-03000 to -03074. Refer to these drawings for detailed geological information. The geological profile is based on the eastbound tunnel in general.
- The vertical alignment and the running tunnel and structure profiles shown are derived from the Alignment S model files: C122-OVE-R4-DMA-CR001-12000 Rev. P09 (dated 26/05/2010), C122-OVE-R4-DMA-CR001_Z-22009 Rev. P19.1 and C122-OVE-C4-DMA-CR001_Z-22001 Rev. P22.1. The cross passages shown are from model file C122-OVE-C4-DMA-CR001_Z-22009 Rev. P14 dated 13/08/2010.
- The ground level shown is derived from model file C122-OVE-R4-DMA-CR001-12000 Rev. P09 (dated 26/05/2010) and bathymetric surveys of West India Dock and River Thames at North Woolwich from Crossrail ground investigations.
- The westbound tunnel is shown where the vertical alignment is significantly different from the eastbound tunnel. The westbound alignment shown is distorted slightly due to the difference between the eastbound and westbound chainages.


Legend:

- Superficial Deposits
- River Terrace Deposits
- London Clay (including Harwich Formation)
- Lambeth Group
- Mid Lambeth Hiatus
- Thanet Sand
- Chalk
- Eastbound Tunnel
- West bound Tunnel
- Cross Passage
- Deep Aquifer Piezometric Level (August 2008)
- Deep Aquifer Piezometric Level (August 2011)
- Groundwater Profile
- Effect of de-watering

Scales:


- Horizontal Scale: 0 to 1000m
- Vertical Scale: 0 to 80m
- Vertical Exaggeration x 10

Figure 3.1.2
 Crossrail Limited
 Crossrail Groundwater Level Monitoring Report - Revision 2
 Geological and Groundwater Profiles



Note:
LW3 (LC(A2)) is not plotted as it is not reliable



Figure 4.3.1




- | | | | | | | | | | |
|------------------|-----------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|-----------------|------------------|
| □ WH5E RTD | ▲ WH6 SND | ▲ WH7R UF | □ WH8CPT RTD | ◆ WH10EB RTD | ■ WH13R (i6) LC-A3 | □ WH13R (i5) LC-A3 | □ WH13R (i4) LC-A2 | ● WH13R (i3) HF | ▲ WH13R (i2) UMB |
| ▲ WH13R (i1) LTB | ● WH14 HF/UMB | ◆ WH16R (i6) LC-A3 | ● WH16R (i5) LC-A3 | ● WH16R (i4) LC-A2 | ■ WH16R (i3) HF | ● WH16R (i2) UMB | □ WH16R (i1) LTB | × WH18 LC(A2) | ■ WH19 LC(A2) |
| ■ WH20 LC(A3) | ▲ WH21R LMB | ◆ WH21R TS | ● WH22 LC(A3) | ■ SG1E RTD | ◆ WH27R TS | ▲ WH27R SND | ■ WH24 LC | ◆ WH24 HF | □ WH24 LTB |
| ▲ WH24 LMB | × WH25R LC (A2) | ■ WH25R LTB | ● WH28R MG | + WH28R UMB | - WH29R RTD | ■ WH29R LC (A2) | ◆ WH32RA HF | ■ WH32RA UF | ▲ WH33R RTD |
| × WH33R LC (A2) | ○ WH33R UMB | + WH33R LTB | × WH33R TS | ▲ WH53R CK | × WH53R LC | | | | |

Note:
 WH4P (CK), WH6 (LC(A2)), WH7R (LC(A2)), WH11R (LC&CK), WH12 (RTD&UMB), WH14 (LC(A3)), WH15(LC(A3)&(A2)), WH17 (UMB) are not plotted as they are not reliable.
 WH33 (LC(A3)) was destroyed during installation

Figure 4.3.2





	Crossrail Limited	Figure 4.3.3
	Crossrail - Groundwater Monitoring Report - Revision 2	
	Ground water levels versus time Route Section D - Whitechapel to Stepney Green	



- | | | | | | | | |
|----------------------|---------------------|---------------------|------------------|--------------------|------------------|----------------------|----------------------|
| ● SG10 HF | ▲ SG12 LTB | □ SG12A LC(A2) | □ SG13 RTD | ◇ SG13 CK | ◆ SG16 LMB | ● SG16 LC (A2) | ■ SG17A LC (A2) |
| ▲ SG17 LTB | ▲ SG19P LMB | × SG14P LTB | ■ SG14P RTD | ◇ SG22 UMB | × SG22 RTD | ● SG24R (i1) LC (A2) | ▲ SG24R (i2) LC (A2) |
| ◇ SG24R (i3) UMB | ◇ SG24R (i4) LTB | ◇ SG24R (i5) LMB | ■ SG24R (i6) UMB | ▲ SG24R (i7) UF/TS | × SG8R (i1) UF | × SG8R (i2) LMB | ● SG8R (i3) SND |
| ▲ SG8R (i4) UMB | ● SG8R (i5) LC (A2) | ○ SG8R (i6) LC (A2) | ◆ SG23R (i1) UF | ■ SG23R (i2) LMB | ▲ SG23R (i3) SND | × SG23R (i4) UMB | × SG23R (i5) LC (A2) |
| ● SG23R (i6) LC (A2) | + SG29 RTD | ● SG29 SND | ■ SG30R UMB | ◆ SG31R RTD | □ SG31R LTB | ▲ SG32R SND | × SG38 SND |
| × SG28R SND | ● SG37R SND | ● SG39R SND | ■ SG33 LMB/UF | □ SG33 SND | □ SG33 SND | ■ SG33 SND | ▲ SG34R UF |
| × SG34R LMB | + SG34R SND | ○ SG34R HF | + SG25R LC(A2) | ■ SG25R UMB | ▲ SG25R UF | ◇ SG25R TS | ■ SG25R TS |


Note:
 SG11R SND, SG11 TS, SG15 LC(A2) and SG15R UF are not plotted as they are not reliable

Figure 4.3.4



	Crossrail Limited	
	Crossrail - Groundwater Monitoring Report - Revision 2	
	Ground water levels versus time Route Section F (to EB Chainage 12300m)	


Figure 4.3.5



- | | | | | | | |
|-----------|----------------------|--------------|-------------|---------------|---------------|-----------|
| BT10E RTD | BT11 TS | BT12R LTB | BT12R RTD | BT15E MG/RTD | BT16R LC (A2) | BT16R USB |
| BT18A RTD | BT18A HF(BHM)/LC(A2) | BT19 LC(A2) | BT20 LC(A2) | BT21E RTD | BT22 LC(A2) | BT23E RTD |
| BT27 LTB | BT33E RTD | BT41 LC (A2) | BT41 RTD | BT53R LC (A2) | BT53R LC (A2) | BT53R UMB |
| BT53R LTB | BT53R LMB | BT53R UF | BT53R TS | BT54R LMB | BT54R LC (A2) | BT55 RTD |

Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2
Ground water levels versus time
 Route Section F (from EB Chainage 12300 to 12800m)

Figure 4.3.6




- | | | | | | | | | | | |
|---------------|-----------------|------------|---------------|-------------|-------------|-------------|--------------|------------|-------------|-------------|
| □ BT24 LC(A3) | □ BT25 RTD | × BT26 RTD | × BT26 LC(A3) | ◆ BT32 UF | ◆ BT34E RTD | + BT38 RTD | ▲ PML16R LTB | ◇ PML25 UF | - BT36R LSB | - BT36R RTD |
| □ BT35R UF | - BT35R LC (A2) | ◆ BT42 UF | ■ BT42 USB | × BT43R RTD | □ BT43R TS | ◆ BT45A RTD | ■ BT45A TS | × BT46 TS | ◆ BT48 LMB | ■ BT48 TS |
| ▲ BT48 TS | + BT49 TS | - BT51R TS | ■ BT51R LMB | ◆ BT52 LC | × BT48 UF | ● BT47R CK | ■ BT47R TS | ▲ BT47R TS | × BT47R UF | × BT44 TS |



Note:
 BT38 (UF), BT29 (UMB), PML 16R (TS) and BT30 (SND) are not plotted as they are not reliable

Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2
Ground water levels versus time
 Route Section F (from EB Chainage 12800 to 13800m)

Figure 4.3.7



Note:
PML1 (LC(A2)) and PML1 (LSB) are not plotted as they are not reliable





Crossrail Limited

Crossrail - Groundwater Monitoring Report - Revision 2


Ground water levels versus time

Route Section G - Pudding Mill Lane

Figure
4.3.9





Note:
IOD12 CK and IOD 20R CK are not plotted as they are unreliable



□ IOD30R CK	□ IOD31P RTD	□ IOD31P CK	▲ IOD30R UF	▲ IOD34R LMB	✕ IOD92R UF/TS	● IOD36R LSB	● IOD36R TS	■ IOD32R LTB	◆ IOD32R UF	◆ IOD40RA TS
■ IOD40RA LSB	▲ IOD82R UF	● IOD84R LTB	■ IOD76R HF	□ IOD100 RTD	◆ IOD102 RTD	▲ IOD104 RTD	□ IOD108 RTD	○ IOD109 RTD	✕ IOD110 RTD	■ IOD111 RTD
● IOD38R CK	▲ IOD38R LMB	+ P57 CK	+ P57 TS	◆ P58 TS	■ P59 TS	▲ P60 CK	■ P60 TS	✕ P61 CK	■ P61 TS	✕ P62 TS
✕ P63 TS	✕ P63 CK	✕ P64 TS	■ P516 RTD	▲ P516 TS	✕ P519 RTD	✕ P519 TS	● PS14 (white) TS	+ PS14 CK	- PS36 (white) TS	- PS36 (black)
◆ PS36 (blue) CK	■ P48 (yellow) TS	▲ P48 (red) CK	✕ P41 TS	■ BP4W5	○ DS3W1	+ P50 TS	- P53 CK	- P53 TS	◆ P54 RTD	■ P55 RTD
▲ P55 TS	✕ P56 TS	✕ IOD112R LSB	✕ IOD112R TS	● IOD113R LTB	+ IOD113R UF	▲ IOD114R RTD	- IOD114R LMB	◆ IOD115R HF	◆ IOD115R HF	■ SP6 CK
▲ SP6 RTD	◆ SP7 TS	✕ SP7 RTD	● SP8 TS	+ SP8 RTD	▲ SP10 TS	- SP10 RTD	◆ SP12 CK	◆ SP12 RTD		


Note:
P514 RTD, P514 TS, P41 RTD, P43 TS and PS14 RTD are not plotted as they are unreliable

Figure 4.3.11



Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2
Ground water levels versus time
 Route Section J (to EB Chainage 15300m)

Figure 4.3.12



- | | | | | | | | | |
|--------------|---------------|----------------|-----------------|---------------|-----------|-----------|---------------|----------------|
| CH10R LC(A2) | CH10R HF(SWM) | CH13 AL | CH13 LTB | CH12R LC (A3) | CH12R SND | CH14R RTD | CH15P LC (A2) | CH15P AL / RTD |
| CH16R LC (B) | CH16R LC (A2) | CH17RA LC (A3) | CH17RA LTB | CH65 AL | CH64 AL | CH62 RTD | CH59 RTD | CH60 AL |
| CH60 RTD | CH73 AL | CH77 AL | CH77 RTD | CH78 RTD | CH87R LSB | CH57R CK | CH70 MG | CH72RC TS |
| CH76A RTD | CH79 RTD | CH79 LC(A2) | CH56RB HF(OHM) | CH61R CK | CH67 MG | CH67 RTD | CH83R TS | CH88R LTB |
| CH89R HF/LTB | CH90R TS | CH91R CK | CH92RA HF (SWM) | CH93R LTB/LSB | | | | |


Crossrail Limited

Crossrail - Groundwater Monitoring Report - Revision 2

Ground water levels versus time

Route Section J (from EB Chainage 15300m to EB Chainage 15900m)

**Figure
4.3.13**



- | | | | | | | | | | | | |
|-------------|-----------|-----------|---------------|--------------|----------|----------|--------------|----------|-----------|-----------|----------|
| CH19 LC(A2) | CH19 SND | CH18R LTB | CH18R LC (A3) | CH22 LC (A2) | CH22 RTD | CH21 HF | CH21 LC (A2) | CH20R CK | CH20R SND | CH48 HF | CH50 RTD |
| CH50 HF/LTB | CH52R RTD | CH52R SND | CH80 LC (A3) | CH80 MG | CH82 RTD | CH81 RTD | CH81 AL | CH82 HF | CHT01 RTD | CHT02 SND | CH96 RTD |
| CH96 SND | CH97 RTD | CH98R AL | CH98R RTD | CH100 RTD | | | | | | | |

Note:
CH49 RTD and CH49 HF are not plotted as no data are available


Figure 4.3.14



- | | | | | | | | | | | | |
|---------------|----------------|----------------|-------------|------------|------------|------------|-----------------|----------------|-------------|------------|---------------|
| □ CH23 AL/RTD | ● CH23 HF | □ CH26R RTD | ▲ CH26R LMB | ● CH34 HF | ■ CH34 RTD | ◇ CH31P CK | ✕ CH31P LC (A2) | ◇ CH37 LC (A2) | — CH37 RTD | ▲ CH38 RTD | ◇ CH38 HF/LTB |
| ✕ CH53 RTD | ● CH53 HF(SWB) | ■ CH54 HF(SWB) | ▲ CH54 RTD | ▲ CH55 RTD | ▲ CH55 HF | ✕ CH68 RTD | ✕ CH69 RTD | ● CHT03 HF | ■ CHT04 RTD | — CHT04 HF | — CHT05 HF |


Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2
Ground water levels versus time
 Route Section K - Victoria Dock Portal

Figure 4.3.15



Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2
Ground water levels versus time
 Route Section L - Victoria Dock Portal to North Woolwich


Figure 4.3.16



- | | | | | | | | | |
|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|--------------|
| ◆ NW11R CK | □ NW11R RTD | ■ NW20P RTD | ◇ NW27R CK | ▲ NWT01 AL | ● NWT01 RTD | □ NWT02 CK | ◆ NWT02 RTD | △ NW30RA RTD |
| ◇ NW30RA CK | ■ NW31R CK | ▲ NW32R CK | × NW32R RTD | × NW33R AL | ● NW33R CK | + NWT05 RTD | + NW49R CK | ● NW50R CK |
| ◇ NW51R RTD | ■ NW52R RTD | ▲ NW53R RTD | ◆ NW53R CK | ● NW54R RTD | ● NW54R CK | ● NW55R RTD | - NW55R CK | × NW56R RTD |
| ◇ NW56R CK | ■ NW57R RTD | ▲ NW57R CK | ● NW58R RTD | ● NW58R CK | □ NW59R CK | ● NW59R RTD | | |

Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2
Ground water levels versus time
 Route Section M - North Woolwich Portal


Figure 4.3.17



□ NW12 RTD
 ◆ NW12 CK
 □ NW16R AL/RTD
 ● NW16R CK
 ◇ NW17 CK
 × NW17 CK
 ◇ NW18R CK
 ■ NW18R CK
 ◆ NW15R CK
 ■ NW15R RTD
 ▲ NWT06 RTD
 ● NW63R CK


Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2
Ground water levels versus time
 Route Section N1 - North Woolwich

Figure 4.3.18



WP88P CK is not plotted as it was destroyed during installation

Figure 4.3.19



Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2
Ground water levels versus time
 Route Section N3 - Woolwich to Plumstead

Figure 4.3.20






Figure 4.3.21













Figure 4.3.25







- | | | | | | | | | | |
|-----------------|-----------------|-------------------|-------------------|------------------|------------------|------------------|-------------------|-----------------|------------------|
| □ BH701 RTD | ◆ BH701 LC (A2) | ▲ BH701 UMB | ● BH704 LC (A3) | ■ BH704 LC (A3) | □ BH704 LC (A2) | □ BH704 LC (A2) | ■ BH704 LMB | ■ BH709 LC (A3) | ▲ BH709 LC (A3) |
| ▲ BH709 LC (A2) | ■ BH709 LC (A2) | ▲ BH709 UMB | ◆ BST17P LC (A2) | ■ BST17P RTD | ■ BST14P LC (A3) | ■ BST14P LC (A2) | ■ BST14P HF (SWM) | ■ BST14P SND | ■ BST14P SND |
| ○ BST14P CK | ▲ BST18RA RTD | × BST18RA LC (A3) | ○ BST18RA LC (A2) | ■ BST18RA UMB | ■ BST18RA UF | ■ BST18RA CK | ■ BST20E AL | ■ BST20E RTD | ■ BST20E RTD |
| ▲ BST22 RTD | × BST22 SND | × BST23R RTD | ● BST23R LC (A3) | ■ BST23R LC (A2) | ■ BST23R SND | ■ BST23R LMB | ■ BST23R TS | ▲ WS268F RTD | ▲ WS268F RTD |
| × WS269 MG | × WS272A MG | ■ BST24R RTD | ■ BST24R LC (A3) | ■ BST24R LC (A2) | ■ BST24R LC (A2) | ■ BST24R UMB | ■ BST24R LMB | ▲ BST24R TS | × BST15R LC (A2) |
| ● BST15R SND | ▲ RT119D LC | + RT119D UMB | ■ BST31R LC (A3) | ■ BST31R SND | ■ BST30R SND | ■ BST30R LTB | ■ BST28R LC (A3) | × BST28R SND | ● BST33R SND |
| + BST33R TS | ■ BST32 LC (A2) | ■ BST32 SND | ◆ BST35R SND | | | | | | |

Note:
BST14P TS not plotted as it is considered unreliable

Figure 4.3.27




- | | | | | | | | | | | | | |
|----------------|-------------|---------------|----------------|----------------|---------------|----------------|----------------|------------|----------------|----------------|----------------|----------------|
| □ T24 CK | ◇ T24 UF | △ T24 LSB | ● T24 HF | ■ T24 LC (A2) | □ T24 LC (A3) | □ T24 RTD | □ T23E RTD | ■ T21R CK | ▲ T21R LMB | ▲ T21R UMB | ■ T21R LC (A2) | ▲ T21R LC (A2) |
| ■ T21R LC (A3) | ◆ T21R RTD | ■ WS295 MG | - WS296 MG | - T19P LC (A3) | ◆ T19P LMB | ■ T20 RTD | ▲ T20 UMB | × T20 TS | × T25R LC (A2) | ● T25R LC (A2) | × T25R LMB | - WS273A MG |
| - WS274 MG | ◆ WS278 RTD | ■ WS310 MG/AL | ▲ T22R LC (A2) | × T22R SND | × T31R UMB | ● T31R LC (A2) | + T26R LC (A2) | - T26R UMB | - T26R LMB | ◆ WS276 RTD | ■ WS277 RTD | |



Note:
RT43 TS not plotted as it is considered unreliable

Figure 4.3.29




- | | | | | | | | | | | | |
|----------------|----------------|---------------|------------------|----------------|------------|----------------|--------------|----------------|-----------------|----------------|----------------|
| ▲ F30R LMB | □ F47 UMB | □ F45 LC (A2) | □ F43 MG/LC (A2) | □ F35R CK | ◆ F35R TS | ▲ F35R LTB | ◆ F35R UMB | □ F35R LC (A2) | ◆ F50R TS | ▲ F50R LMB/UF | ▲ F50R UMB |
| ◆ F50R UMB | □ F50R LC (A2) | ✕ F48 RTD | ✕ F32R LMB/UF | ■ F32R LTB | □ F32R UMB | □ F32R LC (A2) | □ F32R RTD | ▲ F31R LTB | ✕ F31R RTD | ◆ F26R TS | ✕ F26R MG/LC |
| ▲ F57R TS | ▲ F57R LMB | ● F57R UMB | ◆ F53R LTB | □ F53R LC (A2) | ◆ F42R LMB | ▲ F42R UMB | ◆ F34 LMB/UF | ◆ F34 UMB | ✕ F30R UMB | ✕ F30R LC (A2) | ✕ F30R LC (A2) |
| □ F30R CK | ■ F27P CK | ◆ F27P LTB | - F49R LMB | - F49R CK | ◆ F55P LC | ■ F55P TS | ▲ F87 UMB | ✕ F8 UMB | ✕ F8 LMB | ● RT48 UMB | - F3 SND |
| ◆ F7X LSB | ✕ F28 LC | ✕ F28 UMB | ● RT83 SND | + RT83 LMB | - RT84 UMB | - RT84 UF | ◆ F76 LSB | ■ F76 LSB | ▲ F80RA LC (A3) | ✕ F80RA LTB | ✕ F81A LC (A2) |
| ■ F81A LC (A2) | + F81A UMB | - F81A LTB | ■ F82A LTB | ▲ F93R CK | ● BH896 TS | + BH896 CK | - BH896 CK | - BH897 TS | ◆ BH897 CK | ■ BH899 CK | ▲ BH900 MG |
| ■ F67R SND | ● F75 UMB | ● F94 CK | + F30R TS | - F32R TS | - F50R CK | ◆ F67R CK | ■ F92R RTD | | | | |

Note:
RT48 UF, F25 UMB, F25 UF and F4 CK are not plotted as they are considered unreliable



Crossrail Limited
Crossrail - Groundwater Monitoring Report - Revision 2
Ground water levels versus time
Route Section W - Farrington to Liverpool Street


Figure 4.3.30




- | | | | | | | | | | | |
|----------------|------------------|------------|----------------|-----------------|----------------|---------------|------------|------------|-----------|---------------|
| ■ L27P TS | ▲ L30R LC(A2)/HF | ◇ L30R UF | □ L31E RTD | ◆ LW11A UMB/LTB | ◆ LW11A TS | + L25 UF | - L32 UF | ■ L32 UF | ◇ L33 UF | □ L34 UF |
| △ L35R TS | ■ L35R LMB | × L35R LMB | ● L35R UMB | + L36R LTB | - L36R LMB | - L36R UF | ◆ L33RA UF | ■ L34RA UF | ▲ L38R UF | × L46R LC (B) |
| ● L39R LC (A2) | ● L39R UMB | + L47R HF | - L46R LC (A2) | - L40R SND | ◆ L40R LC (A2) | ■ L44 LC (A3) | ▲ L8 RTD | × L21 RTD | × L43 RTD | |

Note:
L8 UMB not plotted as it is not reliable






Crossrail Limited	Figure 4.3.33
Crossrail - Groundwater Monitoring Report - Revision 2	
Borehole Location - Isle of Dogs - Piezometers Logged With Datalogger	




Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2
Isle of Dogs - Rate of recharge of deep aquifer groundwater level between 2007 and 2008

Figure
4.3.34




	Crossrail Limited	Figure
	Crossrail - Groundwater Monitoring Report - Revision 2	
	Isle of Dogs - Rate of drawdown of deep aquifer groundwater level between January and July 2008	4.3.35



- ◆ IOD100 RTD
- IOD102 RTD
- ▲ IOD104 RTD
- IOD108 RTD
- IOD109 RTD
- ✱ IOD110 RTD
- ✱ IOD111 RTD
- ✱ Dock water level

	Crossrail Limited	Figure 4.3.36
	Crossrail - Groundwater Monitoring Report - Revision 2	
	Route Section I - Borehole IOD100-102-104-108-109-110-111 Piezometric Data	


Measured Piezometric Level



¹ Stratigraphic levels based on the average value as reported in GSIR1&2 Rev A, Pk17A and Pk17B.

² ROP1 water level was rising. Last monitoring reading was taken on 29/09/2009. The piezometer is now destroyed.






¹: Stratigraphic levels based on the average value as reported in GSIR1& 2 Rev A, Pk16 & Pk16A data.



Piezometric Pressure (kPa)



1. Stratigraphic levels based on the average value as reported in GSIR1&2 Rev A, Pk16 & Pk16A data.

2. P12RA levels are abnormally high. Possibly influenced by leaky nearby groundwater main.

3. P21R readings to be verified - PK16A




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section R - Paddington Station

Figure

4.4.3



¹ Stratigraphic levels based on the average value as reported in GSIR1&2 Rev A, Pk16 & Pk16A data.
² The stratigraphy lines shown represent the average strata levels encountered to the west and to the east of EB Ch3000m. Text coloured coded to match.
³ Pk16A Piezo RT113R, RT114R & RT115P - reliability to be confirmed




Crossrail Limited
 Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
 Route Section S - Paddington Station to Bond Street

Figure


4.4.4



1. Stratigraphic levels based on the average value as reported in GSIR1&2 Rev A, Pk16 & Pk16A data and BST WTH GI
 2. BH704 (LC(A2) - LMB), BST17P (LC(A2)) and RT119 (LC) thought to be unreliable (piezometers connectivity to upper aquifer); however there is insufficient information to discount their data completely



Piezometric Pressure (kPa)



1. Stratigraphic levels based on the average value as reported in GSIR1&2 Rev A, Pk16 & Pk16A data.
2. T22R(LC A2, SND) are thought to be unreliable piezometers (connectivity to upper aquifer); however there is insufficient information to discount their data completely.
3. Installations with red labels are located in the faulted zone at the east end of the station.




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section U - Tottenham Court Road Station

Figure

4.4.6

Piezometric Pressure (kPa)



1. Stratigraphic levels based on the average value as reported in GSIR1&2 Rev A, Pk16 & Pk16A data.




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section V - Tottenham Court Road Station to Farringdon

Figure

4.4.7

Piezometric Pressure (kPa)



- The stratigraphy lines shown represent the average strata levels encountered in each block on the west side of the main fault/fold zone.
- F27P CK ground water levels thought to be unreliable, this piezometer has been destroyed by demolition work and verification is not possible
- Pk16A piezometers RT132R(TS) - reliability to be confirmed
- RT46XC (LC) - This is located in Route Section V, where the ground level is higher than the Farringdon area.




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section W - Farringdon to Liverpool Street (west of Smithfield Fault, Ref. [36] & [49])

Figure

4.4.8



1. The stratigraphy lines shown represent the average strata levels encountered in each block on the east side of the main fault/fold zone.

2. Pk29 piezometer F81A - preliminary data used; reliability to be confirmed




Crossrail Limited
 Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
 Route Section W - Farringdon to Liverpool Street (east of Smithfield Fault (Block B & C), Ref. [36] & [49])

Figure
4.4.9

Piezometric Pressure (kPa)



1. Stratigraphic levels based on the average value as reported in GSIR1&2 Rev A.
2. L30R (UF) is under observation/investigation.
3. Pk29 and 29VO1 piezometers L33, L34, L38R(UF) and L39A - reliability to be confirmed
4. L19A LTB - investigated; functionality under question.




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section X - Liverpool Street Station

Figure

4.4.10



1. Stratigraphic levels based on the average value as reported in GSIR3 Rev E.

2. LW5 (UMB) and LW15RA (LTB) to be investigated.

3. L19A(LTB) - investigated: functionality under question.




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section A - Liverpool Street to Whitechapel Station

Figure

4.4.11

Piezometric Pressure (kPa)



¹ Stratigraphic levels based on the average value as reported in GSIR3 Rev E.

² WH25R (LC(A2)) and (LTB) to be investigated.




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section C - Whitechapel Station

Figure


4.4.12



¹ Stratigraphic levels based on the average value as reported in GSIR3 Rev E.
² SG44R LC(A2) reliability to be confirmed



Piezometric Pressure (kPa)



¹ Stratigraphic levels based on the average value as reported in GSIR3 Rev E.

² Pk13A piezometers SG29(SND), SG30R(UMB), SG31R(LTB), SG32R(SND), SG34R(SND) and SG38(SND) to be investigated.




Crossrail Limited
 Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
 Route Section E - Stepney Green

Figure


4.4.14



1. Stratigraphic levels based on the average values encountered in the BHs shown in the Figure.

2. BT1(LMB) investigated; functionality under question but insufficient information to discount this data completely.





¹ Stratigraphic levels based on the average values encountered in the BHs shown in the Figure.

² BT11(TS) was last monitored in June 2008.


³ BT9R (SND), BT12R (LTB) and BT27 (LTB) investigated, functionality under question but insufficient information to discount the data completely



Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section F (from EB Chainage 12100 to 13050m, Alignment S)


Figure
4.4.16



Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section F (from EB Chainage 13050 to 13800m, Alignment S)

Figure
4.4.17



1. Stratigraphic levels based on the average value of Route Section G as reported in GSIR3 Rev E.
2. PML4, PML5A and PML17R are located west of the River Lea.
3. PML52R latest reading is "dry"; awaiting confirmation by more data
4. PML28A(SND) to be investigated. However this piezometer has been destroyed and verification not possible




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Sections F (from EB Chainage 13800m, Alignment S) and G

Figure

4.4.18A

Piezometric Pressure (kPa)



1. Stratigraphic levels based on the average value of Route Section G as reported in GSIR3 Rev E.
2. PML4, PML5A and PML17R are located west of the River Lea.
3. PML52R latest reading is "dry"; awaiting confirmation by more data
4. PML28A(SND) to be investigated. However this piezometer has been destroyed and verification is not possible




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Sections F (from EB Chainage 13800m, Alignment S) and G

Figure

4.4.18B



1. Stratigraphic levels based on the average values encountered in the BHs shown in the Figure.

2. IOD19P(TS) was destroyed during remediation work (standpipe jointing broken and leak created in SND). Observed water level consistent with gwp in LG strata.




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section H (to EB Chainage 12400m, Alignment S)

Figure


4.4.19



¹. Stratigraphic levels based on the average values encountered in the BHs shown in the Figure.




Piezometric Pressure (kPa)



1. Stratigraphic levels based on the average value as reported in GSIR4 Rev C.

2. Piezometric profile affected by dewatering activities undergoing in the area.





¹ Stratigraphic levels based on the average values encountered in the BHs shown in the Figure.




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section J (to EB Chainage 14200m, Alignment S)

Figure

4.4.22



¹ Stratigraphic levels based on the average values encountered in the BHs shown in the Figure.

² CH5R, CH10 and CH12R last reading were taken in 2004, 2006 and 2008, respectively since then the profile water level in the deep aquifer has changed.


³ CH6R(CK) is under observation/investigation.



Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section J (from EB Chainage 14200m to 15300m, Alignment S)

Figure
4.4.23



¹ Stratigraphic levels based on the average values encountered in the BHs shown in the Figure.

² This section of the alignment includes a zone of possible faulting.



Crossrail Limited


Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile

Route Section J (from EB Chainage 15300m to 15900m, Alignment S)

Figure

4.4.24A



¹ Stratigraphic levels based on the average values encountered in the BHs shown in the Figure.

² This section of the alignment includes a zone of possible faulting.




Crossrail Limited
 Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
 Route Section J (from EB Chainage 15300m to 15900m, Alignment S)

Figure

4.4.24B



1. Stratigraphic levels based on the average values encountered in the BHs shown in the Figure.
2. CH81 encountered a scour hollow.
3. CH31P (CK) is under observation/investigation.




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section J (from EB Chainage 15900m), K & L (to EB Chainage 17600m, Alignment S)

Figure


4.4.25



¹: Stratigraphic levels based on the average values encountered in the BHs shown in the Figure.



Piezometric Pressure (kPa)



¹ Stratigraphic levels based on the average values encountered in the BHs shown in the Figure.




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section N1 & N2

Figure

4.4.27

Piezometric Pressure (kPa)



¹ Stratigraphic levels based on the average value as reported in GSIR4 Rev C.




Crossrail Limited
Crossrail – Groundwater Monitoring Report

Pore Water Pressure Profile
Route Section N3 - Woolwich to Plumstead


Figure

4.4.28





¹ Stratigraphic levels based on the average value as reported in GSIR4 Rev C.






¹ Stratigraphic levels based on the average values encountered in the BHs shown in the Figure.





Shallow Aquifer Groundwater Level (mATD)


125 123 121 119 117 115 113 111 109 107 105



NOTE:

1. Coordinates and elevations are to LUL grid and height datum.
2. Contours based on Crossrail piezometer readings between 1992-1997.
3. Accuracy of the contours is governed by the available data (positions indicated).
4. Due to the limited database and temporal variations in the shallow aquifer groundwater levels, the contours shown should only be considered as indicative.
5. The courses of the lost rivers shown are approximate based on Barton (1992).

Scale 1:25000



Crossrail Limited



Crossrail - Groundwater Monitoring Report - Revision 2

Shallow aquifer groundwater level contours - (1992-1997)


Royal Oak Portal to Plumstead Portal

Figure

4.5.1



Shallow Aquifer Groundwater Level (mATD)





NOTE:

1. Coordinates and elevations are to LUL grid and height datum.
2. Contours based on Crossrail piezometer readings between 2009 and 2011.
3. Accuracy of the contours is governed by the available data (positions indicated).
4. Due to the limited database and temporal variations in the shallow aquifer groundwater levels, the contours shown should only be considered as indicative.
5. The courses of the lost rivers shown are approximate based on Barton (1992).

Crossrail Limited
Crossrail - Groundwater Monitoring Report - Revision 2


Shallow aquifer groundwater level contours - August 2011
Royal Oak Portal to Plumstead and Pudding Mill Lane Portal

Figure
4.5.2




NOTE:
 1. Coordinates and elevations are to LUL grid and height datum.
 2. Contours based on Crossrail piezometer readings between 2009 and 2011.
 3. Accuracy of the contours is governed by the available data (positions indicated).
 4. Due to the limited database and temporal variations in the shallow aquifer groundwater levels, the contours shown should only be considered as indicative.

Shallow Aquifer Groundwater Level (mATD)



Scale 1:5000






Scour hollow (Berry, 1979)

Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2


Shallow aquifer groundwater level contours - August 2011
 Limmo Peninsula

Figure
4.5.2.b






	Crossrail Limited Crossrail - Groundwater Monitoring Report - Revision 2	Figure 4.5.4.a
	Data showing sesonal Influence Route Section E & F - Stepney Green to Pudding Mill Lane	



	Crossrail Limited Crossrail - Groundwater Monitoring Report - Revision 2	Figure 4.5.4.b
	Data showing sesonal Influence Route Section E & F - Stepney Green to Pudding Mill Lane	



Crossrail Limited


Crossrail - Groundwater Monitoring Report - Revision 2

Route Section G - Borehole PML7 SP - Piezometric Data

Daily Average Piezometric Level and Daily Rainfall

Figure

4.5.5



Crossrail Limited


Crossrail - Groundwater Monitoring Report - Revision 2

Route Section G - Borehole PML8 SP - Piezometric Data


Daily Average Piezometric Level and Daily Rainfall

Figure

4.5.6



	Crossrail Limited	Figure
	Crossrail - Groundwater Monitoring Report - Revision 2	
	Route Section H - Borehole IOD15 - Piezometric Data	4.5.7
	Daily Average Piezometric Level and Daily Rainfall	



Crossrail Limited


Crossrail - Groundwater Monitoring Report - Revision 2

Route Section J - Borehole CH6R - Piezometric Data

Daily Average Piezometric Level and Daily Rainfall

Figure

4.5.8



Crossrail Limited


Crossrail - Groundwater Monitoring Report - Revision 2

Route Section N - Borehole NW12 - Piezometric Data


Daily Average Piezometric Level and Daily Rainfall

Figure

4.5.9



	Crossrail Limited	Figure
	Crossrail - Groundwater Monitoring Report - Revision 2	
	Route Section N - Borehole NW16R - Piezometric Data	4.5.10
	Daily Average Piezometric Level and Daily Rainfall	



Crossrail Limited


Crossrail - Groundwater Monitoring Report - Revision 2

Route Section N - Borehole NW18R - Piezometric Data

Daily Average Piezometric Level and Daily Rainfall

Figure

4.5.11



Crossrail Limited


Crossrail - Groundwater Monitoring Report - Revision 2

Route Section O - Borehole WP21 - Piezometric Data



Daily Average Piezometric Level and Daily Rainfall

Figure

4.5.12



	Crossrail Limited	Figure
	Crossrail - Groundwater Monitoring Report - Revision 2	
	Route Section O - Borehole WP23 - Piezometric Data	4.5.13
	Daily Average Piezometric Level and Daily Rainfall	



NOTE:

1. Coordinates and elevations are to LUL grid and height datum.
2. Contours based on Crossrail piezometer readings August 2011, supplemented with Environment Agency monitoring data for January 2011 and Thames Water London Tideway monitoring data for Dec 2010.
3. Accuracy of the contours is governed by the available data (borehole positions indicated).
4. Due to the limited database and temporal variations in the deep aquifer groundwater levels, the contours shown should only be considered as indicative.



Scale 1:60000



KEY:	
	Location of scour hollows identified by Berry (1979) and Lenham et al. (2006)
	Crossrail borehole / EA / TW monitoring well
	Abstraction Well (location +/- 100m)
	EA Abstraction Well (2010 new licence)
	Expired/Revokated licences (Refer Table 8)
	Groundwater level (mATD)

Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2
Deep aquifer groundwater level contours - August 2011
 Royal Oak Portal and Plumstead Portal


Figure
4.6.1



NOTE:



1. Coordinates and elevations are to LUL grid and height datum.
2. Contours based on Crossrail piezometer readings between August 2011 and September 2010, supplemented with Environment Agency monitoring data.
3. Accuracy of the contours is governed by the available data (borehole positions indicated).
4. Due to the limited database and temporal variations in the deep aquifer groundwater levels, the contours shown should only be considered as indicative.

Scale 1:60000



KEY:		Crossrail borehole / EA / TW monitoring well
		Abstraction Well (location +/- 100m)
		EA Abstraction Well (2010 new licence)
		Expired/Revokated licences (Refer Table 8)
		Rate of change in groundwater level (m/months)

	Crossrail Limited	Figure
	Crossrail - Groundwater Monitoring Report - Revision 2	
	Rate of change of the deep aquifer groundwater level contours - August 2011	4.6.2
	Royal Oak Portal to Plumstead Portal	



- BGS Mapping of LG subcrop
- Locations of scour hollows identified by Berry (1979)
- Port of London Authority Tidal Monitoring gauge

Symbols Key:	Colours Key:
Shallow Aquifer	0m
Strata between shallow and deep aquifer	0 - 0.2m
Deep Aquifer	0.2 - 0.5m
	0.5 - 1.0m
	>1.0m

Note:



- Coordinates and elevations are to LUL grid and height datum.
- Accuracy of the contours is governed by the available data.
- Due to the limited database, the contours shown should only be considered as indicative.
- The locations of the boreholes monitored in the Woolwich, Limmo and Isle of Dogs area are shown in Figures 5, 6 and 7, respectively.



Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2

Tidal influence
 Contours of base of Drift and Summary of tidal monitoring results

Figure
4.7.1





Symbols Key:		Colours Key:	
+	Shallow Aquifer	Black	0m
□	Strata between shallow and deep aquifer	Green	0 - 0.2m
○	Deep Aquifer	Blue	0.2 - 0.5m
		Purple	0.5 - 1.0m
		Red	>1.0m

Note:

- Coordinates and elevations are to LUL grid and height datum.
- Accuracy of the contours is governed by the available data.
- Due to the limited database, the contours shown should only be considered as indicative.



BGS Mapping of LG subcrop
 Locations of Scour Hollows identified by Lenham et al. (2006)



Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2

Tidal influence
 Contours of base of Drift Deposits and Summary of tidal monitoring results - Woolwich to Plumstead

Figure
4.7.2




Symbols Key:

- + Shallow Aquifer
- Strata between shallow and deep aquifer
- Deep Aquifer

Colours Key:

- 0m
- 0 - 0.2m
- 0.2 - 0.5m
- 0.5 - 1.0m
- >1.0m

Contours given in m ATD



Note:

1. Coordinates and elevations are to LUL grid and height datum.
2. Accuracy of the contours is governed by the available data.
3. Due to the limited database, the contours shown should only be considered as indicative.

— BGS Mapping of LG subcrop

⋯ Locations of scour hollows originally identified by Berry (1979) and updated further based on recent geological information

Scale 1:1500



Crossrail Limited



Crossrail - Groundwater Monitoring Report - Revision 2

Tidal influence

Contours of base of Drift Deposits and Summary of tidal monitoring results - Limmo Peninsula

Figure

4.7.3




Symbols Key:

- + Shallow Aquifer
- Strata between shallow and deep aquifer
- Deep Aquifer


Colours Key:

- 0m
- 0 - 0.2m
- 0.2 - 0.5m
- 0.5 - 1.0m
- >1.0m



Note:

1. Coordinates and elevations are to LUL grid and height datum.
2. Accuracy of the contours is governed by the available data.
3. Due to the limited database, the contours shown should only be considered as indicative.





Locations of scour hollows identified by Berry (1979)



Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2
Tidal influence
 Contours of base of Drift and Summary of tidal monitoring results - Isle of Dogs

Figure
4.7.4




Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2
Borehole NW18R (RTD/CK) - Piezometric Data - Example
 Piezometric Response to Tidal Variations

Figure
4.7.5

APPENDIX A:
Crossrail Piezometers – Digital Data

APPENDIX B:


Piezometric groundwater levels of the Piezometers Installed during the 1992 Crossrail Ground Investigations



Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2

1992 Piezometric Data
 Westbourne Park to Paddington

Figure
B1





Crossrail Limited
Crossrail - Groundwater Monitoring Report - Revision 2

1992 Piezometric Data
Praed Street to Balderton Street

Figure

B2




Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2

1992 Piezometric Data
 Bond Street Station

Figure

B3




- | | | | | | | |
|-----------------|----------------|-----------------|-----------------|-----------------|----------------|----------------|
| ◆ T1/Sp (RTD) | ■ T1/Pn (LC) | ▲ T1/Pn (LC) | ✦ T2/Sp (RTD) | ✱ T2/Pn (LC) | ● T3A/Pn (LC) | ┼ T4/St (RTD) |
| — T4/Pn (LMB) | — T5/Sp (CK) | ○ T6/Pn (LC) | ■ T7/Pn (LC) | ▲ T7/Pn (UMB) | ✦ T8/Sp (RTD) | ✱ T8/Pn (LC) |
| — T9/Pn (LC) | — T9/Pn (LC) | — T10/Pn (UMB) | — T11/Pn (UMB) | ◆ T13/Sp (RTD) | ■ T14/Sp (RTD) | ▲ T14/Pn (LC) |
| ✦ T14/Pn (LC) | ✱ T18/Sp (CK) | ● SBT1/Sp (RTD) | ┼ SBT1/Pn (UMB) | — RT20/Pn (LC) | — RT21/Pn (LC) | ◆ RT21/Sp (LC) |
| ■ RT22/St (RTD) | ▲ RT22/Pn (LC) | ✦ RT22/Pn (LC) | ✱ RT23/Pn (LC) | — RT24/St (RTD) | — RT24/Pn (LC) | |

Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2

1992 Piezometric Data
 Argyll Street to Tottenham Court Road Station


Figure
B4



Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2

1992 Piezometric Data
 Charing Cross Road to Red Lion Square


Figure
B5



Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2

1992 Piezometric Data
 Red Lion Square to Farringdon Road

Figure
B6




Crossrail Limited
Crossrail - Groundwater Monitoring Report - Revision 2

1992 Piezometric Data
Farringdon Station

Figure


B7



Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2

1992 Piezometric Data
 Aldersgate Street to Moor Lane

Figure
B8



Crossrail Limited


Crossrail - Groundwater Monitoring Report - Revision 2

1992 Piezometric Data

Liverpool Street Station

Figure


B9



Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2

1992 Piezometric Data
 Bishopsgate to Allen Gardens

Figure
B10



Crossrail Limited
 Crossrail - Groundwater Monitoring Report - Revision 2

1992 Piezometric Data
 Allen Gardens to Vallance Road

Figure
B11

APPENDIX C:
**Summary of Problems Identified with Piezometers Installed during the 1992 Crossrail
Ground Investigations**

BH No.	Piezo Type	Coordinates		Location	CrossFall (historic)			Norwest Holst (May 2004)			GCG (May 2006)			GCG (Dec 2006)			GCG (June 2008)			GCG (March 2010)		GCG (September 2010)		GCG (August 2011)		Comments
		Easting	Northing		Operation	Depth to tip (m)	Water level (m)	Operation	Depth to tip (m)	Water level (m)	Operation	Depth to tip (m)	Water level (m)	Operation	Depth to tip (m)	Water level (m)	Operation	Depth to tip (m)	Water level (m)	Operation	Piezometer Status	Operation	Piezometer Status	Operation	Piezometer Status	
Paddington Station																										
P1	Pn	76761.48	36250.52	Eastbourne Terrace (opposite No.10)	NW	16.90	destroyed	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
P2	Pn	76806.47	36180.36	Eastbourne Terrace (opposite No.20)	NW	27.00	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
P3	Pn	76842.28	36161.32	Eastbourne Terrace (outside No.20)	NW	48.50	17.00	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	Road resurfaced
P4	Sp	76842.28	36161.32	Eastbourne Terrace (outside No.20)	NW	39.50	17.00	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	Road resurfaced
P5	Pn	76937.72	36034.66	Eastbourne Terrace (outside No.50)	NW	19.00	damaged	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
P6	Pn	76867.64	36111.43	Eastbourne Terrace (outside No.40)	NW	34.80	broken	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
P7	St	76992.28	36114.7	Paddington Station BR (Lawn concourse)	?	4.30	dry	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Destroyed	SNV	Destroyed	SNV	Destroyed	Lawn no longer exists. Area developed into shopping centre.
P7	Pn	76992.28	36114.7	Paddington Station BR (Lawn concourse)	?	38.50	32.00	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Destroyed	SNV	Destroyed	SNV	Destroyed	Lawn no longer exists. Area developed into shopping centre.
P8	Sp	76980.5	36139.98	Paddington Station BR (Lawn concourse)	?	3.85	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Destroyed	SNV	Destroyed	SNV	Destroyed	Lawn no longer exists. Area developed into shopping centre.
P8	Pn	76980.5	36139.98	Paddington Station BR (Lawn concourse)	?	13.80	9.30	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Destroyed	SNV	Destroyed	SNV	Destroyed	Lawn no longer exists. Area developed into shopping centre.
P9	St	77027.62	36060.33	Prad Street (outside GWR Hotel)	?	6.80	6.10	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	not located	SNV	not located	SNV	not located	Area resurfaced.
P11	St	76945.02	36189.66	Paddington Station BR (platform)	?	4.80	3.90	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	not located	SNV	not located	SNV	not located	
P11	Pn	76945.02	36189.66	Paddington Station BR (platform)	?	20.90	13.50	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
SBP1	Pn	76980.5	36139.63	Eastbourne Terrace (outside No.40)	?	22.10	broken	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
SB2	Pn	76132.23	36463.62	London Taxi area	?	10.00	6.43	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
Bond Street Station																										
B1	Pn	78803.48	35841.68	Gilbert Street (outside Moore Flats)	?	33.50	waterlogged	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
B2	Pn	78802.31	35882.11	South Molton Street (outside No.36)	?	24.50	destroyed	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
B3	Pn	78886.18	35855.12	Davies Street (corner of South Molton Lane)	OK	20.50	destroyed	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
B3	Pn	78886.18	35855.12	Davies Street (corner of South Molton Lane)	OK	47.80	destroyed	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
B4	Sp	78888.1	35815.89	Davies Street (outside No.65)	OK	6.50	dry	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	not located/considered destroyed	SNV	not located/considered destroyed	SNV	Considered Destroyed	Road resurfaced
B4	Pn	78888.1	35815.89	Davies Street (outside No.65)	OK	16.00	broken	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Destroyed	SNV	Destroyed	SNV	Destroyed	Road resurfaced
B4	Sp	78888.1	35815.89	Davies Street (outside No.65)	OK	39.50	broken	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Destroyed	SNV	Destroyed	SNV	Destroyed	Road resurfaced
B5	St	78843.05	35787.61	St. Anselm's Place (opposite No.27)	OK	5.90	tarmaced over	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	tarmaced over	SNV	Considered Destroyed	SNV	Considered Destroyed	Road resurfaced
B5	Sp	78843.05	35787.61	St. Anselm's Place (opposite No.27)	OK	22.00	tarmaced over	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	tarmaced over	SNV	Considered Destroyed	SNV	Considered Destroyed	Road resurfaced
B5	Pn	78843.05	35787.61	St. Anselm's Place (opposite No.27)	NW	38.50	broken	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Destroyed	SNV	Destroyed	SNV	Destroyed	Road resurfaced
B6	Sp	78949.28	35846.08	South Molton Street (outside No.50)	NW	13.00	damaged	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Destroyed	SNV	Destroyed	SNV	Destroyed	Road resurfaced
B6	Pn	78949.28	35846.08	South Molton Street (outside No.50)	NW	30.50	broken	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Destroyed	SNV	Destroyed	SNV	Destroyed	Road resurfaced
B7	Sp	79048.54	35812.56	Haund of Venison Yard (outside No.3)	OK	23.00	tarmaced over	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	tarmaced over	SNV	Considered Destroyed	SNV	Considered Destroyed	Road resurfaced
B8	Sp	79124.12	35875.33	Tanterden Street (outside No.1)	NW	11.00	destroyed	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Destroyed	SNV	Destroyed	SNV	Destroyed	Road resurfaced
B8	Pn	79124.12	35875.33	Tanterden Street (outside No.1)	OK	35.50	not located	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	Road resurfaced
B9	Pn	79201.76	35853.85	Hanover Square (outside No.20)	NW	28.00	destroyed	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Destroyed	SNV	Destroyed	SNV	Destroyed	Road resurfaced
B10	Pn	79198.2	35907.81	Hanover Square (outside No.15)	?	22.00	10.90	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
B11	Pn	79161.13	35806.31	Brook Street (outside No.8 to 12)	OK	12.30	0.10	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	Last reading considered unreliable.
B12	St	79265.5	35854.07	Hanover Square (opposite No.4)	NW	6.80	tarmaced over	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	tarmaced over	SNV	Considered Destroyed	SNV	Considered Destroyed	Inspection is blocked by car
B12	Sp	79265.5	35854.07	Hanover Square (opposite No.4)	NW	27.00	tarmaced over	NL	-	NL	-	NL	-	NL	-	NL	-	NL	-	NL	tarmaced over	SNV	Considered Destroyed	SNV	Considered Destroyed	Inspection is blocked by car
B12	Pn	79265.5	35854.07	Hanover Square (opposite No.4)	NW	44.50	broken	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	Inspection is blocked by car
B13	Pn	79370.8	35869.74	Hanover Square (opposite No.20)	NW	9.00	destroyed	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Destroyed	SNV	Destroyed	SNV	Destroyed	
B13	Pn	79370.8	35869.74	Hanover Square (opposite No.20)	NW	18.00	destroyed	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Destroyed	SNV	Destroyed	SNV	Destroyed	
SB1	Pn	78887.09	35818.85	Davies Street (outside No.65)	?	18.00	obstructed	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
Tottenham Court Road Station																										
T1	Sp	79943.33	35976.02	Carlisle Street (outside No.4)	?	8.70	not located	NL	-	NL	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	not located	SNV	not located	SNV	not located	
T1	Pn	79943.33	35976.02	Carlisle Street (outside No.4)	NW	13.50	broken	NL	-	NL	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Destroyed	SNV	Destroyed	SNV	Destroyed	
T1	Pn	79943.33	35976.02	Carlisle Street (outside No.4)	OK	23.50	not located	NL	-	NL	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	
T2	Sp	79882.12	36070.4	Great Chapel Street (outside No.3 to 4)	NW	9.30	silted	NL	-	NL	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	Road resurfaced
T2	Pn	79882.12	36070.4	Great Chapel Street (outside No.3 to 4)	?	21.90	no return flow	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	Road resurfaced
T3A	Pn	79918.2	36077.64	Dean Street (outside No.1)	NW	18.00	broken	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Destroyed	SNV	Destroyed	SNV	Destroyed	
T4	St	79894.06	36019.37	Great Chapel Street (outside No.15 to 19)	NW	8.30	broken	NL	-	NL	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Destroyed	SNV	Destroyed	SNV	Destroyed	Road resurfaced
T4	Pn	79894.06	36019.37	Great Chapel Street (outside No.15 to 19)	NW	39.50	broken	NL	-	NL	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Destroyed	SNV	Destroyed	SNV	Destroyed	Road resurfaced
T5	Sp	80043.82	36062.64	Soho Square (opposite No.14)	OK	61.50	blocked	NL	-	NL	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	Road resurfaced
T5	Pn	80037.78	36076.87	Soho Square (opposite No.30)	OK	15.90	broken	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Considered Destroyed	SNV	Considered Destroyed	SNV	Considered Destroyed	Road resurfaced
T7	Pn	80157.5	36073.2	Sutton Row (next to the Astoria)	NW	20.50	broken	SNV	-	NL	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Destroyed	SNV	Destroyed	SNV	Destroyed	
T7	Pn	80157.5	36073.2	Sutton Row (next to the Astoria)	NW	28.85	broken	SNV	-	NL	-	SNV	-	SNV	-	SNV	-	SNV	-	SNV	Destroyed	SNV	Destroyed	SNV	Destroyed	
T8	Sp	80216.9	36009.3	Denmark Street (outside No.19)	?	5.00	4.76	NL	-	NL	-	SNV	-	SNV	-	SN										

